

## Long Life Cermet Potentiometer up to 2 Million Cycles



Their excellent performances are due to the use of a cermet-track sealed in a large case.

P13 interchangeability with RV6, combined with the excellent stability of its rated characteristics make it fully acceptable for industrial and professional uses.

### FEATURES



- 2 million cycles for bushing L and N
- 1 million cycles for bushing T, Q, O, and P
- High power rating 1.5 W at 70 °C
- Test according to CECC 41000 or IEC 60393-1
- Cermet element
- Fully sealed case
- Mechanical strength
- Compliant to RoHS Directive 2002/95/EC
- Custom designs on request




**RoHS**  
COMPLIANT

### DIMENSIONS in millimeters ( $\pm 0.5$ )



#### P13LT




#### Panel Cutout





#### P13LQ




#### Panel Cutout






#### P13LL



#### Panel Cutout



**ELECTRICAL SPECIFICATIONS**

Resistive Element	Cermet																													
Electrical Travel	270° ± 10°																													
Standard Resistance Value	1 kΩ - 5 kΩ - 10 kΩ - 50 kΩ																													
Tolerance	± 20 %																													
Taper																														
Circuit Diagram																														
Power Rating	<div>Linear 1.5 W at 70 °C</div> <div>Logarithmic 0.75 W at 70 °C</div> 																													
Standard Resistance Element Data	<table><tr><th rowspan="2">Resistance Value (kΩ)</th><th colspan="2">Linear Taper</th><th colspan="2">Non-Linear Taper</th></tr><tr><th>Max. Power at 70 °C (W)</th><th>Max. Working Voltage (V)</th><th>Max. Power at 70 °C (W)</th><th>Max. Working Voltage (V)</th></tr><tr><td>1</td><td>1.5</td><td>38.7</td><td>0.75</td><td>27.4</td></tr><tr><td>5</td><td>1.5</td><td>86.6</td><td>0.75</td><td>61.2</td></tr><tr><td>10</td><td>1.5</td><td>122</td><td>0.75</td><td>87</td></tr><tr><td>50</td><td>1.5</td><td>274</td><td>0.75</td><td>194</td></tr></table>	Resistance Value (kΩ)	Linear Taper		Non-Linear Taper		Max. Power at 70 °C (W)	Max. Working Voltage (V)	Max. Power at 70 °C (W)	Max. Working Voltage (V)	1	1.5	38.7	0.75	27.4	5	1.5	86.6	0.75	61.2	10	1.5	122	0.75	87	50	1.5	274	0.75	194
Resistance Value (kΩ)	Linear Taper		Non-Linear Taper																											
	Max. Power at 70 °C (W)	Max. Working Voltage (V)	Max. Power at 70 °C (W)	Max. Working Voltage (V)																										
1	1.5	38.7	0.75	27.4																										
5	1.5	86.6	0.75	61.2																										
10	1.5	122	0.75	87																										
50	1.5	274	0.75	194																										
Temperature Coefficient (Typical)	± 150 ppm/°C																													
Limiting Element Voltage (Linear Law)	350 V																													
End Resistance (Typical)	1 Ω																													
Dielectric Strength (RMS)	2000 V																													
Insulation Resistance (300 V <sub>DC</sub> )	10 <sup>6</sup> MΩ																													
Independent Linearity (Typical)	± 5 %																													







### MECHANICAL SPECIFICATIONS

Mechanical Travel	300° ± 5°	
Operating Torque (Typical)	2 Ncm max.	2.85 oz. inch max.
End Stop Torque		
Style T, Q	35 Ncm max.	3.1 lb inch max.
Style L	80 Ncm max.	7.1 lb inch max.
Tightening Torque of Mounting Nut		
Style T, Q	150 Ncm max.	13.3 lb inch max.
Style L	250 Ncm max.	22.1 lb inch max.
Unit Weight	6 g to 18 g max.	0.22 oz. to 0.64 oz.
Terminals	e3: Pure Sn	

### ENVIRONMENTAL SPECIFICATIONS

Temperature Range	- 55 °C to 125 °C
Climatic Category	55/125/56
Sealing	Fully sealed - Container IP67

### OPTIONS

Special Feature Command Shaft	Length is measured from the mounting surface to the free end of the shaft. The screwdriver slot is aligned with the wiper within ± 10°. Special shafts are available, in accordance to drawings supplied by customers. We recommend that customers should not machine tool shafts, in order to avoid damage. Bending or torsion of terminals should also be avoided.
Panel Sealing	<p>Potentiometers P13LT and P13LL can be fitted with a device providing sealing between the threaded bushing and the front panel. Their designation is P13LP and P13LN respectively or with a locating peg P13LP...E and P13LN...E.</p> <p><b>Panel sealed version</b> <b>P13LP</b> <b>P13LP...E: Including locating peg</b></p>   <p><b>Panel Cutout</b></p>  <p><b>Panel sealed version</b> <b>P13LN</b> <b>P13LN...E: Including locating peg</b></p>   <p><b>Panel Cutout</b></p> 


## OPTIONS

### Shaft Locking

On potentiometers equipped with a 3 mm Ø shaft, shaft locking can be obtained:

- Either by a taper nut tightening a slotted bushing. Ask for P13LO type. These devices are normally equipped with an AB type shaft (12.5 mm with a slot).


#### P13LO



- Or by a tightening nut locked by a screw. Ask for ES1 type. On potentiometers equipped with a Ø 6 mm shaft, locking can be obtained by a taper nut applying pressure on a slotted notched washer. This device is supplied in a box as an accessory. Ask for DBAN.

These devices are ordered separately. Please consult Vishay Sfernice.

#### P13LL DBAN



No locking on shaft Ø 4 mm.

## MARKING

Printed:


- Vishay trademark
- Part number (including ohmic value code, tolerance code and taper)
- Manufacturing date code
- Marking of terminals a

## APPLICATION NOTE

The potentiometer shall be used in voltage divider with an impedance load at least 100 times higher than the total potentiometer nominal resistance value.

Advised load impedance:

1 MΩ min. for resistance range of 1 kΩ to 50 kΩ



## PACKAGING

- In box of 8 pieces for shafts FR and FQ
- In box of 10 pieces for shafts FE, FL, FG, and FK
- In box of 15 pieces for shafts AJ and EJ
- In box of 25 pieces for shafts AB, AA, EA, and EB

**Long Life Cermet Potentiometer  
up to 2 Million Cycles****Vishay Sfernice****PERFORMANCE**

TESTS	CONDITIONS	TYPICAL VALUES AND DRIFTS		
		$\Delta R_T/R_T$ (%)	$\Delta R_{1-2}/R_{1-2}$ (%)	OTHER
Electrical Endurance	1000 h at rated power 90°/30° - ambient temp. 70 °C	± 20 %	± 20 %	-
Climatic Sequence	Phase A dry heat 125 °C Phase B damp heat Phase C cold - 55 °C Phase D damp heat 5 cycles	± 0.5 %	± 1 %	-
Damp Heat, Steady State	56 days 40 °C 93 % HR	± 0.5 %	± 1 %	Dielectric strength: 1000 V Insulation resistance: > 10 <sup>4</sup> MΩ
Change of Temperature	5 cycles - 55 °C at + 125 °C	± 0.5 %	-	-
Mechanical Endurance	Bushings L and N: 2 000 000 cycles Bushings T, Q, O, and P: 1 000 000 cycles at rated power Turn angle ± 60° Temperature ± 20 °C	± 20 %	-	Independent linearity: ± 10 %
Shock	50 g's at 11 ms 3 successive shocks in 3 directions	± 0.1 %	± 0.2 %	-
Vibration	10 Hz to 55 Hz 0.75 mm or 10 g's during 6 h	± 0.1 %	-	$\Delta V_{1-2}/V_{1-3} < \pm 0.2$ %

**ORDERING INFORMATION (Part Number)**

VISHAY 2000 1000 500 200 100 50 20 10 5 2 1 0.5 0.2 0.1 0.05 0.02 0.01 0.005 0.002 0.001 0.0005 0.0002 0.0001 0.00005 0.00002 0.00001 0.000005 0.000002 0.000001 0.0000005 0.0000002 0.0000001 0.00000005 0.00000002 0.00000001 0.000000005 0.000000002 0.000000001 0.0000000005 0.0000000002 0.0000000001 0.00000000005 0.00000000002 0.00000000001 0.000000000005 0.000000000002 0.000000000001 0.0000000000005 0.0000000000002 0.0000000000001 0.00000000000005 0.00000000000002 0.00000000000001 0.000000000000005 0.000000000000002 0.000000000000001 0.0000000000000005 0.0000000000000002 0.0000000000000001 0.00000000000000005 0.00000000000000002 0.00000000000000001 0.000000000000000005 0.000000000000000002 0.000000000000000001 0.0000000000000000005 0.0000000000000000002 0.0000000000000000001 0.00000000000000000005 0.00000000000000000002 0.00000000000000000001 0.000000000000000000005 0.000000000000000000002 0.000000000000000000001 0.0000000000000000000005 0.0000000000000000000002 0.0000000000000000000001 0.00000000000000000000005 0.00000000000000000000002 0.00000000000000000000001 0.000000000000000000000005 0.000000000000000000000002 0.000000000000000000000001 0.0000000000000000000000005 0.0000000000000000000000002 0.0000000000000000000000001 0.00000000000000000000000005 0.00000000000000000000000002 0.00000000000000000000000001 0.000000000000000000000000005 0.000000000000000000000000002 0.000000000000000000000000001 0.0000000000000000000000000005 0.0000000000000000000000000002 0.0000000000000000000000000001 0.00000000000000000000000000005 0.00000000000000000000000000002 0.00000000000000000000000000001 0.000000000000000000000000000005 0.000000000000000000000000000002 0.000000000000000000000000000001 0.0000000000000000000000000000005 0.0000000000000000000000000000002 0.0000000000000000000000000000001 0.00000000000000000000000000000005 0.00000000000000000000000000000002 0.00000000000000000000000000000001 0.000000000000000000000000000000005 0.000000000000000000000000000000002 0.000000000000000000000000000000001 0.0000000000000000000000000000000005 0.0000000000000000000000000000000002 0.0000000000000000000000000000000001 0.00000000000000000000000000000000005 0.00000000000000000000000000000000002 0.00000000000000000000000000000000001 0.000000000000000000000000000000000005 0.000000000000000000000000000000000002 0.000000000000000000000000000000000001 0.0000000000000000000000000000000000005 0.0000000000000000000000000000000000002 0.0000000000000000000000000000000000001 0.00000000000000000000000000000000000005 0.00000000000000000000000000000000000002 0.00000000000000000000000000000000000001 0.000000000000000000000000000000000000005 0.000000000000000000000000000000000000002 0.000000000000000000000000000000000000001 0.0000000000000000000000000000000000000005 0.0000000000000000000000000000000000000002 0.0000000000000000000000000000000000000001 0.005 0.002 0.001 0.0005 0.0002 0.0001 0.005 0.002 0.001 0.0005 0.0002 0.0001 0.005 0.002 0.001 0.0005 0.0002 0.0001 0.005 0.002 0.001 0.0005 0.0002 0.0001 0.005 0.002 0.001 0.0005 0.0002 0.0001 0.005 0.002 0.001 0.0005 0.0002 0.0001 0.005 0.002 0.001 0.0005 0.0002 0.0001 0.005 0.002 0.001 0.0005 0.0002 0.0001 0.005 0.002 0.001 0.0005 0.0002 0.0001 0.005 0.002 0.001 0.0005 0.0002 0.0001 0.005 0.002 0.001 0.0005 0.0002 0.0001 0.005 0.002 0.001 0.0005 0.0002 0.0001 0.005 0.002 0.001 0.0005 0.0002 0.0001 0.005 0.002 0.001 0.0005 0.0002 0.0001 0.005 0.002 0.001 0.0005 0.0002 0.0001 0.005 0.002 0.001 0.0005 0.0002 0.0001 0.005 0.002 0.001 0.0005 0.0002 0.0001 0.005 0.002 0.001 0.0005 0.0002 0.0001 0.005 0.002 0.001 0.0005 0.0002 0.0001 0.005 0.002 0.001 0.0005 0.0002 0.0001 0.005 0.002 0.001 0.0005 0.0002 0.0001 0.005 0.002 0.001 0.0005 0.0002 0.0001 0.005 0.002 0.001 0.0005 0.0002 0.0001 0.005 0.002 0.001 0.00																
---	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--

**PART NUMBER DESCRIPTION (for information only)**

P13L	Q	E	EA	10K	20 %	L		BO25			e3
MODEL	BUSHING	SPECIAL	SHAFT	VALUE	TOLERANCE	TAPER	SPECIAL	PACKAGING	SHAFT	SPECIAL	LEAD (Pb)-FREE



## Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and/or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.

## Material Category Policy

**Vishay Intertechnology, Inc. hereby certifies that all its products that are identified as RoHS-Compliant fulfill the definitions and restrictions defined under Directive 2011/65/EU of The European Parliament and of the Council of June 8, 2011 on the restriction of the use of certain hazardous substances in electrical and electronic equipment (EEE) - recast, unless otherwise specified as non-compliant.**

**Please note that some Vishay documentation may still make reference to RoHS Directive 2002/95/EC. We confirm that all the products identified as being compliant to Directive 2002/95/EC conform to Directive 2011/65/EU.**

**Vishay Intertechnology, Inc. hereby certifies that all its products that are identified as Halogen-Free follow Halogen-Free requirements as per JEDEC JS709A standards. Please note that some Vishay documentation may still make reference to the IEC 61249-2-21 definition. We confirm that all the products identified as being compliant to IEC 61249-2-21 conform to JEDEC JS709A standards.**