





A
B
C
D
E
F
G
H

A
B
C
D
E
F
G
H



E243711 (UL) SJT 3X14AWG(2.08mm²) VW-1 SHIELDED 60°C 300V CSA 228191 SJ
T 3X14AWG(2.08mm²) FT2 SHIELDED 60°C 300V -LF-

- NOTES:
 1) JACKET COLOR: BLACK
 2) .E-GREEN; L-BLACK ; N-WHITE
- TESTING:
 1) 100% OPEN & SHORT TESTING
 2) INSULATION RESISTANCE: 100M ohm(min)
 3) VOLTAGE: DC500V/1min
 4) ROHS COMPLIANT

NO.	SPECIFICATION	COLOUR	MATERIAL	AMOUNT
①	Load terminals 98661	Silver	Cu	2P
②	Grounding terminal 97475	Silver	Cu	1P
③	Model aircraft 8661AN-3P	WHITE	PBT	1PCS
④	Plug JLL-301	BLACK	PVC Cu	1PCS
⑤	Wire SJT 14AWG/3C 60°C	BLACK	PVC Cu	1PCS
⑥	Ties	BLACK		1PCS

Scale	1:1						Name	Item No.
TOLERANCE							Miller	A-PC2314-030029-1
X.X	±0.40				Drawn	3/26/12		
X.XX	±0.25				Approved	3/26/12	Warner	Title 5-15P to Open, 3M, SJT#14*3C 60C SHIELDED
X.XXX	±0.15							Drawing No.
Angle	±3°							rev00
		Modification	Date	Name				

