


## General Description

KEC NPT Trench IGBTs offer low switching losses, high energy efficiency and short circuit ruggedness.

It is designed for applications such as motor control, uninterrupted power supplies(UPS), general inverters.

## FEATURES

- High speed switching
- High system efficiency
- Short Circuit Withstand Times 10us
- Extremely enhanced avalanche capability




## MAXIMUM RATING (Ta=25 °C)

CHARACTERISTIC	SYMBOL	RATING	UNIT
Collector-Emitter Voltage	$V_{CES}$	600	V
Gate-Emitter Voltage	$V_{GES}$	± 20	V
Collector Current	$I_C$	@Tc=25	80 A
		@Tc=100	40 A
Pulsed Collector Current	$I_{CM}^*$	120	A
Diode Continuous Forward Current	@Tc=100 $I_F$	40	A
Diode Maximum Forward Current	$I_{FM}$	80	A
Maximum Power Dissipation	$P_D$	@Tc=25	290 W
		@Tc=100	116 W
Maximum Junction Temperature	$T_j$	150	
Storage Temperature Range	$T_{stg}$	-55 to + 150	

\*Repetitive rating : Pulse width limited by max. junction temperature

## THERMAL CHARACTERISTIC

CHARACTERISTIC	SYMBOL	MAX.	UNIT
Thermal Resistance, Junction to Case (IGBT)	$R_{thJC}$	0.43	/W
Thermal Resistance, Junction to Case (DIODE)	$R_{thJC}$	1.45	/W
Thermal Resistance, Junction to Ambient	$R_{thJA}$	40	/W




# KGT40N60KDA

## ELECTRICAL CHARACTERISTICS (Ta=25 )

CHARACTERISTIC	SYMBOL	TEST CONDITION	MIN.	TYP.	MAX.	UNIT	
<b>Static</b>							
Collector-Emitter Breakdown Voltage	$BV_{CES}$	$V_{GE}=0V, I_C=250\mu A$	600	-	-	V	
Collector Cut-off Current	$I_{CES}$	$V_{GE}=0V, V_{CE}=600V$	-	-	250	$\mu A$	
Gate Leakage Current	$I_{GES}$	$V_{CE}=0V, V_{GE}=\pm 20V$	-	-	$\pm 100$	nA	
Gate Threshold Voltage	$V_{GE(th)}$	$V_{GE}=V_{CE}, I_C=250\mu A$	4.5	5.5	7.0	V	
Collector-Emitter Saturation Voltage	$V_{CE(sat)}$	$V_{GE}=15V, I_C=40A$	-	1.80	2.20	V	
		$V_{GE}=15V, I_C=40A, T_C = 125$	-	2.10	-	V	
		$V_{GE}=15V, I_C=80A, T_C = 25$	-	2.45	-	V	
<b>Dynamic</b>							
Total Gate Charge	$Q_g$	$V_{CC}=400V, V_{GE}=15V, I_C= 40A$	-	170	-	nC	
Gate-Emitter Charge	$Q_{ge}$		-	25	-	nC	
Gate-Collector Charge	$Q_{gc}$		-	80	-	nC	
Turn-On Delay Time	$t_{d(on)}$	$V_{CC}=300V, I_C=40A, V_{GE}=15V, R_G=10$ Inductive Load, $T_C = 25$	-	50	-	ns	
Rise Time	$t_r$		-	40	-	ns	
Turn-Off Delay Time	$t_{d(off)}$		-	170	-	ns	
Fall Time	$t_f$		-	35	-	ns	
Turn-On Switching Loss	$E_{on}$		-	0.6	-	mJ	
Turn-Off Switching Loss	$E_{off}$		-	0.4	-	mJ	
Total Switching Loss	$E_{ts}$		-	1.0	-	mJ	
Turn-On Delay Time	$t_{d(on)}$		$V_{CC}=300V, I_C=40A, V_{GE}=15V, R_G=10$ Inductive Load, $T_C = 125$	-	55	-	ns
Rise Time	$t_r$			-	50	-	ns
Turn-Off Delay Time	$t_{d(off)}$			-	185	-	ns
Fall Time	$t_f$	-		75	-	ns	
Turn-On Switching Loss	$E_{on}$	-		1.2	-	mJ	
Turn-Off Switching Loss	$E_{off}$	-		1.0	-	mJ	
Total Switching Loss	$E_{ts}$	-		2.2	-	mJ	
Input Capacitance	$C_{ies}$	$V_{CE}=30V, V_{GE}=0V, f=1MHz$	-	3200	-	pF	
Output Capacitance	$C_{oes}$		-	200	-	pF	
Reverse Transfer Capacitance	$C_{res}$		-	100	-	pF	
Short Circuit Withstand Time	$t_{sc}$	$V_{CC}=300V, V_{GE}=15V, T_C=100$	10	-	-	$\mu s$	

Note 1 : Energy loss include tail current and diode reverse recovery.

### Marking



- ① Device Mark 1
- ② Device Mark 2
- ③ Lot No

# KGT40N60KDA

## ELECTRICAL CHARACTERISTIC OF DIODE

CHARACTERISTIC	SYMBOL	TEST CONDITION		MIN.	TYP.	MAX.	UNIT
Diode Forward Voltage	$V_F$	$I_F = 40A$	$T_C = 25$	-	1.8	2.3	V
			$T_C = 125$	-	1.5	-	
Diode Reverse Recovery Time	$t_{rr}$	$I_F = 40A$	$T_C = 25$	-	90	-	ns
			$T_C = 125$	-	105	-	
Diode Peak Reverse Recovery Current	$I_{rr}$	$I_F = 40A$ $di/dt = -600A/\mu s$	$T_C = 25$	-	16	-	A
			$T_C = 125$	-	29	-	
Diode Reverse Recovery Charge	$Q_{rr}$	$I_F = 40A$ $di/dt = -600A/\mu s$	$T_C = 25$	-	730	-	nC
			$T_C = 125$	-	1550	-	

# KGT40N60KDA

Fig 1. Saturation Voltage Characteristics




Fig 2. Saturation Voltage Characteristics




Fig 3. Saturation Voltage vs. Case Temperature




Fig 4. Saturation Voltage vs.  $V_{GE}$




Fig 5. Saturation Voltage vs.  $V_{GE}$





Fig 6. Capacitance Characteristics



# KGT40N60KDA

Fig 7. Turn-On Characteristics vs. Gate Resistance




Fig 8. Turn-Off Characteristics vs. Gate Resistance




Fig 9. Switching Loss vs. Gate Resistance




Fig 10. Turn-On Characteristics vs. Collector Current




Fig 11. Turn-Off Characteristics vs. Collector Current





Fig 12. Switching Loss vs. Collector Current



# KGT40N60KDA

Fig 13. Gate Charge Characteristics




Fig 14. SOA Characteristics




Fig 15. Turn-Off SOA





Fig 16. Transient Thermal Impedance of IGBT



# KGT40N60KDA

Fig 17. Forward Characteristics




Fig 18. Reverse Recovery Current




Fig 19. Reverse Recovery Time

