# BGA Heat Sink (High Aspect Ratio Ext.) **Slant Fin**





ATS Part#:

Description:

#### ATS035035004-MF-11C

35.00 x 35.00 x 4.00 mm BGA Heat Sink (High Aspect Ratio Ext.) Slant Fin

Heat Sink Type: Slant Fin Heat Sink Attachment: N/A Equivalent Part Number: N/A

\*Image above is for illustration purpose only.

#### **Features & Benefits**

- Features a low profile, slant fin array that offers many of the performance benefits of maxiFLOW™ at a great value
- Fabricated from extruded aluminum, which minimizes thermal resistance from the base to the fins, reduces weight and keeps costs low .
- . Higher performance helps ensure reliable product life at a lower cost than other extruded heat sinks
- Comes standard without interface material or with most common pressure sensitive thermal tapes as a custom option ٠

### **Thermal Performance**

AIR VELOCITY		@200 LFM 1.0 M/S	@300 LFM 1.5 M/S	@400 LFM 2.0 M/S	@500 LFM 2.5 M/S	@600 LFM 3.0 M/S	@700 LFM 3.5 M/S	@800 LFM 4.0 M/S
THERMAL RESISTANCE	Unducted Flow	25.92 °C/W	19.2 °C/W	14.6 °C/W	11.8 °C/W	10.1 °C/W	9 °C/W	8.3 °C/W
	Ducted Flow	7.2	6	5.3	4.8	4.5	4.2	3.9

## **Product Detail**

Schematic Image	Dimension A	Dimension B	Dimension C	Dimension D	тім	Finish
	35.00 mm	35.00 mm	4.00 mm	35.71 mm	N/A	BLACK-ANODIZED
	<ul> <li>Dimension</li> <li>Dimension</li> <li>Thermal papplication</li> <li>ATS resension</li> <li>ATS resension</li> <li>ATS certifier</li> </ul>	n <b>D</b> is fin tip to fin tip performance data are n. rves the right to upda nce.	e provided for refere ate or change its pro k assembly is RoHS	m of the base to the nce only. Actual perf ducts without notice 6-6 and REACH com ble.	formanc to impr	e may vary by
*Image above is for illustration purpose only.						

For more information, to find a distributor or to place an order, please contact us at 781-769-2800 (North America), sales@qats.com or www.qats.com.



© 2013 Advanced Thermal Solutions, Inc. | 89-27 Access Road | Norwood MA | 02062 | USA