


Omnimate Range - Pitch 7.50 mm



Socket blocks BLZ 7.50/270B



Technical Data		VDE	UL	CSA
Rated voltage	V	500*	300	300
Rated current	A	13	10	10
Clamping range max.	mm ² /AWG	2.5	12	12
*Overvoltage category III / Pollution severity 3				
Additional technical data see page 226				

Colour



Poles	Type	Cat. No.	Cat. No.	Qty.
2	BLZ 7.50/2/270B	1702450000	1702560000	100
3	BLZ 7.50/3/270B	1702460000	1702570000	100
4	BLZ 7.50/4/270B	1702470000	1702580000	100
5	BLZ 7.50/5/270B	1702480000	1702590000	50
6	BLZ 7.50/6/270B	1702490000	1702600000	50
7	BLZ 7.50/7/270B	1702500000	1702610000	50
8	BLZ 7.50/8/270B	1702510000	1702620000	50
9	BLZ 7.50/9/270B	1702520000	1702630000	50
10	BLZ 7.50/10/270B	1702530000	1702640000	50
11	BLZ 7.50/11/270B	1702540000	1702650000	50
12	BLZ 7.50/12/270B	1702550000	1702660000	50

Accessories	Page
Fixing	193
Marking	196
Coding	199
Miscellaneous	207