




**Advanced Power  
Electronics Corp.**

**AP03N70H/J-H**

**RoHS-compliant Product**

*N-CHANNEL ENHANCEMENT MODE  
POWER MOSFET*



- ▼ 100% Avalanche Test
- ▼ Fast Switching Speed
- ▼ Simple Drive Requirement
- ▼ RoHS Compliant



$BV_{DSS}$	700V
$R_{DS(ON)}$	4.4Ω
$I_D$	2.5A

## Description

The TO-252 package is widely preferred for all commercial-industrial surface mount applications and suited for AC/DC converters. The through-hole version (AP03N70J) is available for low-profile applications.



## Absolute Maximum Ratings

Symbol	Parameter	Rating	Units
$V_{DS}$	Drain-Source Voltage	700	V
$V_{GS}$	Gate-Source Voltage	+30	V
$I_D @ T_C = 25^\circ C$	Continuous Drain Current, $V_{GS} @ 10V$	2.5	A
$I_D @ T_C = 100^\circ C$	Continuous Drain Current, $V_{GS} @ 10V$	1.6	A
$I_{DM}$	Pulsed Drain Current <sup>1</sup>	8	A
$P_D @ T_C = 25^\circ C$	Total Power Dissipation	54.3	W
	Linear Derating Factor	0.44	W/°C
$E_{AS}$	Single Pulse Avalanche Energy <sup>2</sup>	31	mJ
$I_{AR}$	Avalanche Current	2.5	A
$T_{STG}$	Storage Temperature Range	-55 to 150	°C
$T_J$	Operating Junction Temperature Range	-55 to 150	°C

## Thermal Data

Symbol	Parameter	Value	Units
$R_{thj-c}$	Maximum Thermal Resistance, Junction-case	2.3	°C/W
$R_{thj-a}$	Maximum Thermal Resistance, Junction-ambient	110	°C/W



## Electrical Characteristics@ $T_j=25^\circ\text{C}$ (unless otherwise specified)

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Units
$\text{BV}_{\text{DSS}}$	Drain-Source Breakdown Voltage	$\text{V}_{\text{GS}}=0\text{V}$ , $\text{I}_D=1\text{mA}$	700	-	-	V
$\Delta \text{BV}_{\text{DSS}}/\Delta T_j$	Breakdown Voltage Temperature Coefficient	Reference to $25^\circ\text{C}$ , $\text{I}_D=1\text{mA}$	-	0.6	-	V/ $^\circ\text{C}$
$\text{R}_{\text{DS(ON)}}$	Static Drain-Source On-Resistance <sup>3</sup>	$\text{V}_{\text{GS}}=10\text{V}$ , $\text{I}_D=1.6\text{A}$	-	-	4.4	$\Omega$
$\text{V}_{\text{GS(th)}}$	Gate Threshold Voltage	$\text{V}_{\text{DS}}=\text{V}_{\text{GS}}$ , $\text{I}_D=250\mu\text{A}$	2	-	4	V
$\text{g}_{\text{fs}}$	Forward Transconductance	$\text{V}_{\text{DS}}=10\text{V}$ , $\text{I}_D=1.6\text{A}$	-	2	-	S
$\text{I}_{\text{DSS}}$	Drain-Source Leakage Current	$\text{V}_{\text{DS}}=600\text{V}$ , $\text{V}_{\text{GS}}=0\text{V}$	-	-	10	$\mu\text{A}$
	Drain-Source Leakage Current ( $T_j=150^\circ\text{C}$ )	$\text{V}_{\text{DS}}=480\text{V}$ , $\text{V}_{\text{GS}}=0\text{V}$	-	-	100	$\mu\text{A}$
$\text{I}_{\text{GSS}}$	Gate-Source Leakage	$\text{V}_{\text{GS}}=\pm 30\text{V}$	-	-	$\pm 100$	nA
$\text{Q}_g$	Total Gate Charge <sup>3</sup>	$\text{I}_D=1\text{A}$	-	12	20	nC
$\text{Q}_{\text{gs}}$	Gate-Source Charge	$\text{V}_{\text{DS}}=480\text{V}$	-	3	-	nC
$\text{Q}_{\text{gd}}$	Gate-Drain ("Miller") Charge	$\text{V}_{\text{GS}}=10\text{V}$	-	4	-	nC
$t_{\text{d(on)}}$	Turn-on Delay Time <sup>3</sup>	$\text{V}_{\text{DD}}=300\text{V}$	-	8.5	-	ns
$t_r$	Rise Time	$\text{I}_D=2.5\text{A}$	-	6	-	ns
$t_{\text{d(off)}}$	Turn-off Delay Time	$\text{R}_G=10\Omega$ , $\text{V}_{\text{GS}}=10\text{V}$	-	19	-	ns
$t_f$	Fall Time	$\text{R}_D=120\Omega$	-	8	-	ns
$\text{C}_{\text{iss}}$	Input Capacitance	$\text{V}_{\text{GS}}=0\text{V}$	-	590	950	pF
$\text{C}_{\text{oss}}$	Output Capacitance	$\text{V}_{\text{DS}}=25\text{V}$	-	50	-	pF
$\text{C}_{\text{rss}}$	Reverse Transfer Capacitance	$f=1.0\text{MHz}$	-	6	-	pF
$\text{R}_g$	Gate Resistance	$f=1.0\text{MHz}$	-	3.4	5.1	$\Omega$

## Source-Drain Diode

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Units
$\text{V}_{\text{SD}}$	Forward On Voltage <sup>3</sup>	$\text{I}_S=2.5\text{A}$ , $\text{V}_{\text{GS}}=0\text{V}$	-	-	1.5	V
$t_{\text{rr}}$	Reverse Recovery Time <sup>3</sup>	$\text{I}_S=2.5\text{A}$ , $\text{V}_{\text{GS}}=0\text{V}$ ,	-	407	-	ns
$\text{Q}_{\text{rr}}$	Reverse Recovery Charge	$d\text{I}/dt=100\text{A}/\mu\text{s}$	-	2110	-	nC

### Notes:

- 1.Pulse width limited by Max. junction temperature.
- 2.Starting  $T_j=25^\circ\text{C}$  ,  $\text{V}_{\text{DD}}=50\text{V}$  ,  $\text{L}=10\text{mH}$  ,  $\text{R}_G=25\Omega$  ,  $\text{I}_{\text{AS}}=2.5\text{A}$ .
- 3.Pulse test

THIS PRODUCT IS SENSITIVE TO ELECTROSTATIC DISCHARGE, PLEASE HANDLE WITH CAUTION.

USE OF THIS PRODUCT AS A CRITICAL COMPONENT IN LIFE SUPPORT OR OTHER SIMILAR SYSTEMS IS NOT AUTHORIZED.

APEC DOES NOT ASSUME ANY LIABILITY ARISING OUT OF THE APPLICATION OR USE OF ANY PRODUCT OR CIRCUIT DESCRIBED HEREIN; NEITHER DOES IT CONVEY ANY LICENSE UNDER ITS PATENT RIGHTS, NOR THE RIGHTS OF OTHERS.

APEC RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY, FUNCTION OR DESIGN.




Fig 1. Typical Output Characteristics




Fig 2. Typical Output Characteristics



Fig 3. Normalized  $BV_{DSS}$  v.s. Junction Temperature

Fig 4. Normalized On-Resistance v.s. Junction Temperature




Fig 5. Forward Characteristic of Reverse Diode




Fig 6. Gate Threshold Voltage v.s. Junction Temperature

# AP03N70H/J-H







Fig 9. Maximum Safe Operating Area





Fig 11. Switching Time Waveform

Fig 12. Gate Charge Waveform