





		OI HOII IOIIII	THE C NO C MITTERS C	offer wind fire of di
	PARAMETER		TEST CONDITIONS	VALUE
(6B)	D.C. RESISTANCE	S-F	@20°C	0.57 ohms max.
	INDUCTANCE	S-F	100kHz, 100mVAC, Ls	750uH ±20%

GENERAL SPECIFICATIONS: CURRENT RATING: 250mADC.

It is recommended that the 750311431 Inductor be secured to the PCB with epoxy.

CUSTOMER TERMINAL RoHS LEAD(Pb)-FREE Sn96%, Ag4% Yes Yes WE-MIDCOM LOT CODE & DATE CODE 750311431 .365 MAX. (6B) [9.27] .580 MAX. [14.73] TINNING AND INSULATION .200 ±.050 ±.050 FROM BOTTOM [5.08 ±1.27] OF COIL ø.015 TYP.(2) .260 TYP. [.38] [6.60]



DETAILS SUBJECT TO CHANGE

REV.	DATE	Packaging Specifications			
6D	4/11	Method: Tray OC. 0788 (60)			
6C	12/10	1 1 1 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2			
6B	6/10	www.we-online.com/midcom			
6A	4/10	SEE REVISION SHEET FOR REVISION LEVEL			

Tolerances unless otherwise specified: Angles: ±1° Decimals: ±.005 [.13] Fractions: ±1/64 Footprint:

This drawing is dual dimensioned. Dimensions in brackets are in millimeters.

DRAWING TITLE

INDUCTOR

eiSos p/n: **750311431**

PART NO.

750311431



Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Wurth Electronics: 750311431