

Two and Three Conductor Bantam Patch Cords


Bantam patch cords are plastic jacketed, shielded cords with molded-on plugs. The plugs are made with molded insulation between conductors. Bantam patch cords are available with single and dual, two or three conductor plug configurations. A cord strain relief feature is included in the plug construction. Dual twisted pair patch cords are recommended for protection against cross talk, especially during switch cutovers and when patch cords over 12' are used.



Two Conductor Single Patch Cord



Two Conductor
Dual Patch Cord



Three Conductor Single Patch Cord



Three Conductor Dual Patch Cord

^{**}Nickel plated dual patch cords will exhibit loss of plating at 500 insertion/withdrawals.

Ordering Information	
Description	Catalog Number
Two Conductor	
Single 1' (.3 m) 1.5' (.46 m) 2' (.61 m) 3' (.91 m) 4' (1.22 m) 5' (1.52 m) 6' (1.83 m) Dual	PJ702 PJ703 PJ704 PJ706 PJ708 PJ710 PJ1206
1' (.3 m) 2' (.61 m) 2.5' (.76 m) 3' (.91 m) 4' (1.22 m) 5' (1.52 m) 6' (1.83 m)	PJ752 PJ754 PJ755 PJ756 PJ758 PJ760 PJ1306
Three Conductor* Single	
1' (.3 m) 1.5' (.46 m) 2' (.61 m) 2.5' (.76 m) 3' (.91 m) 4' (1.22 m) 5' (1.52 m) 6' (1.83 m) 8' (2.44 m) 10' (3.05 m) 12' (3.66 m) 15' (4.57 m) 20' (6.1 m) 25' (7.62 m) 30' (9.15 m) 50' (15.24 m)	PJ712 PJ713 PJ714 PJ715 PJ716 PJ718 PJ720 PJ122 PJ1210 PJ1212 PJ1415 PJ1420 PJ1425 PJ1430 PJ1450
Dual** 1' (.3 m) 2' (.61 m) 2.5' (.76 m) 3' (.91 m) 4' (1.22 m) 5' (1.52 m) 6' (1.83 m) 8' (2.44 m) 10' (3.05 m) 12' (2.66 m) 14' (4.27 m) 20' (6.1 m) 25' (7.62 m) 30' (9.15 m) 35' (10.68 m) 45' (13.73 m)	PJ762 PJ764 PJ765 PJ766 PJ768 PJ770 PJ1308 PJ1310 PJ1312 PJ1514 PJ1520 PJ1525 PJ1535 PJ1535
Dual (Twisted Pair)	PJ1303TP
15' (4.57 m) 20' (6.1 m) 25' (7.62 m)	PJ1315TP PJ1320TP PJ1325TP

For additional patch cord lengths, contact ADC at 1-800-366-3891, Ext. 3475.

^{*}For nickel plated patch cords, add the suffix "N". For plenum-rated fire retardant patch cords, add the suffix "PL".