

ATE1GGPC7 Product Details

[Live Product Chat](#)



ATE1GGPC7
(1-1437557-3)

TE Internal Number: 1-1437557-3

[Superseded](#)

[Contact Product Information Center](#)

Toggle Switches

[Not EU RoHS or ELV Compliant](#)

Product Highlights:

- ATE Series
- Single Pole - Double Throw Configuration (Pole-Throw)
- Current Rating = 0.4 VA Amps.
- Mount Style = Through-Hole
- Termination Type = Vertical

[View all Features](#)

Quick Links

- [Check Pricing & Availability](#)
- [Search for Tooling](#)
- [Product Feature Selector](#)
- [Contact Us About This Product](#)

[Add to My Part List](#) [Request Sample](#) [Find Similar Products](#) [Buy Product](#)

Documentation & Additional Information	
<p>Product Drawings:</p> <ul style="list-style-type: none"> • None Available <p>Catalog Pages/Data Sheets:</p> <ul style="list-style-type: none"> • ALCOSWITCH PRODUCTS (PDF, English) <p>Product Specifications:</p> <ul style="list-style-type: none"> • None Available <p>Application Specifications:</p> <ul style="list-style-type: none"> • None Available <p>Instruction Sheets:</p> <ul style="list-style-type: none"> • None Available <p>CAD Files:</p> <ul style="list-style-type: none"> • None Available 	<p>Additional Information:</p> <ul style="list-style-type: none"> • Product Line Information <p>Additional Product Images:</p> <ul style="list-style-type: none"> • Dimensional Drawing <p>Related Products:</p> <ul style="list-style-type: none"> • Tooling

[List all Documents](#)

Product Features (Please use the Product Drawing for all design activity)	
<p>Product Type Features:</p> <ul style="list-style-type: none"> • Configuration (Pole-Throw) = Single Pole - Double Throw • Termination Type = Vertical • Comment = Terminals Connected 2-3 and 5-6; 2-1 and 5-4 <p>Electrical Characteristics:</p> <ul style="list-style-type: none"> • Current Rating (Amps.) = 0.4 VA <p>Termination Related Features:</p> <ul style="list-style-type: none"> • Seal Type = Terminal Seal (epoxy), Internal Actuator "O" Ring <p>Body Related Features:</p> <ul style="list-style-type: none"> • Series = ATE • Mount Style = Through-Hole • Flammability Rating = UL 94V-0 <p>Contact Related Features:</p> <ul style="list-style-type: none"> • Contact Plating = Gold over Nickel 	<p>Housing Related Features:</p> <ul style="list-style-type: none"> • Toggle Style = Baton Long • Toggle Length (mm [in]) = 10.00 [0.394] • Process Sealed = Yes • Bushing Style = Unthreaded • Bushing Type = Plain <p>Configuration Related Features:</p> <ul style="list-style-type: none"> • Operating Function = (On) Off (On) <p>Industry Standards:</p> <ul style="list-style-type: none"> • RoHS/ELV Compliance = Not ELV/RoHS compliant • Lead Free Solder Processes = Wave solder capable to 240°C <p>Other:</p> <ul style="list-style-type: none"> • Brand = Alcoswitch

Corporate Information

- [Who We Are](#)
- [Investors](#)
- [News Room](#)
- [Supplier Portal](#)
- [Careers](#)

Quick Links

- [Check Distributor Inventory](#)
- [Cross Reference](#)
- [Find Documents & Drawings](#)
- [Product Compliance Support Center](#)
- [Site Map](#)

Customer Support

- [Email or Chat with Us](#)
- [Find a Phone Number](#)
- [Search Knowledge Base](#)
- [Manage Your Account](#)