


# L 237 200 Power connectors


► Expert Range



Female socket.  
Vertical socket soldered on P.C.B.  
Modular mounting (panel or through panel mounting).

Pin 0.8 x 1 x 3.5 mm  
.031" x .039" x .138"  
P.C.B. thickness ≤ 2.4 mm .094"  
P.C.B. holes Ø 1.5 mm .059"  
Body : UL94 V0 - PC  
Grey □

## Spacing 7.62 mm .300"



### Part numbers


N. Poles	Weight kg	Packaging	L. mm	Order code
<b>Without flange :</b>				
4	0.0111	30	39.90	1SSA 237 204 R0100
6	0.0167	20	55.10	1SSA 237 206 R0100
8	0.0223	20	70.40	1SSA 237 208 R0100
Other numbers of poles, consult us				
<b>With flanges :</b>				
4	0.0133	30	59.70	1SSA 237 204 R3100
6	0.0189	20	74.90	1SSA 237 206 R3100
8	0.0245	20	90.20	1SSA 237 208 R3100
Other numbers of poles, consult us				

### Technical characteristics

	IEC	UL	CSA
Wire size			
Rated voltage	380 V	300 V	300 V
Rated current	25 A	15 A	20 A
Short-circuit current			
Rated wire size / Gauge			
Storage temperature range	-20 ~ +80 °C		
Insulation resistance	≥ 10 <sup>9</sup> Ω		
Wire stripping length			
Recommended screwdriver			
Recommended torque			
Protection			



Socket L 237 200 compatible with :



### Accessories

Rep.	Description	Type	Order code	L. mm	Packaging	Weight kg
1	Housing grey □	4 poles	1SSA 299 004 R0100	50.30 mm		
	grey □	6 poles	1SSA 299 004 R0200	65.50 mm		
	grey □	8 poles	1SSA 299 004 R0300	80.80 mm		

### Other versions, please consult us :

Female plug. Wire Wrapping.

