

ZIF CONNECTORS IN 1.25 MM (.050") PITCH

PHYSICAL PROPERTIES

INSULATION MATERIAL: Polyester glass reinforced
UL 94V-O
CONTACT MATERIAL: Brass
NUMBER OF POSITIONS: 3 to 30

ELECTRICAL PROPERTIES

VOLTAGE RATING: 200 VAC
CURRENT RATING: 0,5 A
CONTACT RESISTANCE: 20 mΩ (max.)
INSULATION RESISTANCE: 1000 MΩ (min)


ENVIRONMENTAL PROPERTIES

OPERATING TEMPERATURE: -40° C to +85° C





R-Version

right angled






PCB Pattern



S-Version

straight



PRODUCT NO.	NO. OF POSITIONS	DIMENSIONS IN MM (INCHES)	
		A	B
FPC 125-03-X	03	05.20 (0.203)	09.60 (0.374)
FPC 125-04-X	04	06.45 (0.252)	10.80 (0.421)
FPC 125-05-X	05	07.70 (0.300)	12.10 (0.472)
FPC 125-06-X	06	08.95 (0.349)	13.35 (0.521)
FPC 125-07-X	07	10.20 (0.398)	14.60 (0.569)
FPC 125-08-X	08	11.45 (0.447)	15.85 (0.618)
FPC 125-09-X	09	12.70 (0.495)	17.10 (0.667)
FPC 125-10-X	10	13.95 (0.544)	18.35 (0.716)
FPC 125-11-X	11	15.20 (0.593)	19.60 (0.764)
FPC 125-12-X	12	16.45 (0.642)	20.85 (0.813)
FPC 125-13-X	13	17.70 (0.690)	22.10 (0.862)
FPC 125-14-X	14	18.95 (0.739)	23.35 (0.911)
FPC 125-15-X	15	20.20 (0.788)	24.60 (0.959)
FPC 125-16-X	16	21.45 (0.837)	25.85 (1.008)
FPC 125-17-X	17	22.70 (.885)	27.10 (1.057)
FPC 125-18-X	18	23.95 (.934)	28.35 (1.106)
FPC 125-19-X	19	25.20 (.983)	29.60 (1.154)
FPC 125-20-X	20	26.45 (1.032)	30.85 (1.203)
FPC 125-21-X	21	27.70 (1.080)	32.10 (1.252)
FPC 125-22-X	22	28.95 (1.129)	33.35 (1.301)
FPC 125-23-X	23	30.20 (1.178)	34.60 (1.349)
FPC 125-24-X	24	31.45 (1.227)	35.85 (1.398)
FPC 125-25-X	25	32.70 (1.275)	37.10 (1.447)
FPC 125-26-X	26	33.95 (1.324)	38.35 (1.496)
FPC 125-27-X	27	35.20 (1.373)	39.60 (1.544)
FPC 125-28-X	28	36.45 (1.422)	40.85 (1.593)
FPC 125-29-X	29	37.70 (1.470)	42.10 (1.642)
FPC 125-30-X	30	38.95 (1.519)	43.35 (1.691)

Dimensions of FLEX Flat Cable

