



1) Einlotstifte passend für Lochungen  $\phi 1 \pm 0,1$  nach IEC 60326-3  
 Solder pins for PCB connections  $\phi 1 \pm 0,1$  as per IEC 60326-3  
 A souder pour des trous de  $\phi 1 \pm 0,1$  selon IEC 60326-3

A	09195147322	3	4,5							 All Dim. in mm Orig. Size DIN A 4	SEK 19 Male connector 14 poles, low profile, high temperature with straight pins	Maßstab/ Scale 1.5:1			
	09195146322	2	4,5				Detail.	25-APR-02	CV						
	09195145322	0.76 $\mu\text{m Au}$	4,5				Insp.								
	09195147324	3	2,9				Stand.								
	09195146324	2	2,9				HARTING EURL F-95972 Paris							TB 0919514x32x	Blatt/ Page 1 / 2
	09195145324	0.76 $\mu\text{m Au}$	2,9	29778	25-APR-02	CV									
	Part-No.	performance level	0	Mod.	Dat.	Name				Sub.					

**09 19 514 6324**  
**IDC male connector**

Other applications

Connector size	14 contacts
Termination	Straight solder pin
Profile	Low-profile male header
Moulding	High Temperature Material
Termination length	2.9 mm
Performance level	Performance level 2



Data sheets are available in following formats

2D files

Typenblatt

Typenblatt

**09 19 514 5324**  
**IDC male connector**

Other applications

Connector size	14 contacts
Termination	Straight solder pin
Profile	Low-profile male header
Moulding	High Temperature Material
Termination length	2.9 mm
Performance level	AU-0.76 μ m [30 μ Inch]

[Inquiry](#)

The data sheet is up to date

2D files

[PDF](#)

[DXF](#)

**09 19 514 7324**  
**IDC male connector**

Other applications

Connector size	14 contacts
Termination	Straight solder pin
Profile	Low-profile male header
Moulding	High Temperature Material
Termination length	2.9 mm
Performance level	Performance level 3

[Inquiry](#)

The data sheet is up to date

2D files

[PDF](#)

[DXF](#)