




Unimate Range - SLA/BLA



Pin headers SLA 5.08/90



Technical data	VDE	UL	CSA
Rated voltage (V)	250*	300	300
Rated current (A)	10	10	10




*Pollution severity 3 / Overvoltage category III
Additional technical data see page 227

Solder pin length 4.5 mm

Color	Poles	Type	Part No.	Qty.
	2	SLA 5.08/2/90	1346860000	100
	3	SLA 5.08/3/90	1346960000	100
	4	SLA 5.08/4/90	1347060000	100
	5	SLA 5.08/5/90	1347160000	50
	6	SLA 5.08/6/90	1347260000	50
	7	SLA 5.08/7/90	1347360000	50
	8	SLA 5.08/8/90	1347460000	50
	9	SLA 5.08/9/90	1347560000	50
	10	SLA 5.08/10/90	1347660000	50
	11	SLA 5.08/11/90	1347760000	50
	12	SLA 5.08/12/90	1347860000	50
	13	SLA 5.08/13/90	1347960000	50
	14	SLA 5.08/14/90	1348060000	50
	15	SLA 5.08/15/90	1348160000	50
	16	SLA 5.08/16/90	1348260000	50
	17	SLA 5.08/17/90	1348360000	20
	18	SLA 5.08/18/90	1348460000	20
	19	SLA 5.08/19/90	1348560000	20
	20	SLA 5.08/20/90	1348660000	20
	21	SLA 5.08/21/90	1348760000	20
	22	SLA 5.08/22/90	1348860000	20
	23	SLA 5.08/23/90	1348960000	20
	24	SLA 5.08/24/90	1349060000	20

Accessories	Page
Mounting	-
Marking	190
Coding	193
Miscellaneous	199

Pin headers SLA 5.08/90B



Technical data	VDE	UL	CSA
Rated voltage (V)	250*	300	300
Rated current (A)	10	10	10




*Pollution severity 3 / Overvoltage category III
Additional technical data see page 227

Solder pin length 4.5 mm

Color	Poles	Type	Part No.	Qty.
	2	SLA 5.08/2/90B	1351460000	100
	3	SLA 5.08/3/90B	1351560000	100
	4	SLA 5.08/4/90B	1351660000	100
	5	SLA 5.08/5/90B	1351760000	50
	6	SLA 5.08/6/90B	1351860000	50
	7	SLA 5.08/7/90B	1351960000	50
	8	SLA 5.08/8/90B	1352060000	50
	9	SLA 5.08/9/90B	1352160000	50
	10	SLA 5.08/10/90B	1352260000	50
	11	SLA 5.08/11/90B	1352360000	50
	12	SLA 5.08/12/90B	1352460000	50
	13	SLA 5.08/13/90B	1352560000	50
	14	SLA 5.08/14/90B	1352660000	50
	15	SLA 5.08/15/90B	1352760000	50
	16	SLA 5.08/16/90B	1352860000	50
	17	SLA 5.08/17/90B	1352960000	20
	18	SLA 5.08/18/90B	1353060000	20
	19	SLA 5.08/19/90B	1353160000	20
	20	SLA 5.08/20/90B	1353260000	20
	21	SLA 5.08/21/90B	1353360000	20
	22	SLA 5.08/22/90B	1353460000	20
	23	SLA 5.08/23/90B	1353560000	20
	24	SLA 5.08/24/90B	1353660000	20

Accessories	Page
Mounting	187**
Marking	190
Coding	193
Miscellaneous	199

Pin headers SLA 5.08/180



Technical data	VDE	UL	CSA
Rated voltage (V)	250*	300	300
Rated current (A)	10	10	10

*Pollution severity 3 / Overvoltage category III
Additional technical data see page 227

Solder pin length 4.5 mm

Color	Poles	Type	Part No.	Qty.
	2	SLA 5.08/2/180	1349160000	100
	3	SLA 5.08/3/180	1349260000	100
	4	SLA 5.08/4/180	1349360000	100
	5	SLA 5.08/5/180	1349460000	50
	6	SLA 5.08/6/180	1349560000	50
	7	SLA 5.08/7/180	1349660000	50
	8	SLA 5.08/8/180	1349760000	50
	9	SLA 5.08/9/180	1349860000	50
	10	SLA 5.08/10/180	1349960000	50
	11	SLA 5.08/11/180	1350060000	50
	12	SLA 5.08/12/180	1350160000	50
	13	SLA 5.08/13/180	1350260000	50
	14	SLA 5.08/14/180	1350360000	50
	15	SLA 5.08/15/180	1350460000	50
	16	SLA 5.08/16/180	1350560000	50
	17	SLA 5.08/17/180	1350660000	20
	18	SLA 5.08/18/180	1350760000	20
	19	SLA 5.08/19/180	1350860000	20
	20	SLA 5.08/20/180	1350960000	20
	21	SLA 5.08/21/180	1351060000	20
	22	SLA 5.08/22/180	1351160000	20
	23	SLA 5.08/23/180	1351260000	20
	24	SLA 5.08/24/180	1351360000	20

Accessories	Page
Mounting	-
Marking	190
Coding	193
Miscellaneous	-