

# MTC 6



## VMT with Intel Atom® Processor and Voice Kit

- Three display types: 10.4" SVGA, 12.1" XGA or 15" XGA
- Fully rugged, IP 67 for the complete system
- Advantech-DLoG-specific resistive touch screen
- WLAN with integrated diversity antenna
- Advantech-DLoG Voice Kit (microphone/speaker), optionally
- Extreme temperature cycles
- Optimum protection against Shock/Vibration

## Introduction

The MTC 6 is a rugged vehicle mount terminal that increases efficiency in logistics – in the distribution center, port, or warehouse, and even in the deep-freeze area. Equipped with WLAN diversity, the MTC 6 offers the advantage that – particularly in demanding environments – the data connection remains safe and reliable, even in fast roaming situations.

## Specifications

System	CPU	Intel Atom® 1.1 GHz
	Memory	1 GB RAM
	Storage	starting at 4 GB Flash media
Housing	coated aluminium, fanless design	
Dimensions/Weight	MTC 6/10	285 x 229 x 78 mm, 3 kg / 11.2 x 9.0 x 3.1 in, 6.6 lbs
	MTC 6/12	325 x 258 x 79 mm, 3.5 kg / 12.8 x 10.1 x 3.1 in, 7.7 lbs
	MTC 6/15	388 x 305 x 82 mm, 4.9 kg / 15.3 x 12.0 x 3.2 in, 10.9 lbs
Display	MTC 6/10	10.4" LED, SVGA 800 x 600
	MTC 6/12	12.1" LED, XGA 1024 x 768
	MTC 6/15	15" LED, XGA 1024 x 768
Front Keys	8 soft keys (incl. 4 configurable function keys)	
Touch Screen	Advantech-DLoG-specific resistive Touch Screen	
Software	Operating System	MS® Windows® XP Professional, XP Embedded, WES 7
	Emulations	VT100, VT220, IBM 5250, TN 3270, Citrix ICA Client®, RDP Client
Communication	WLAN	IEEE 802.11 a/b/g/n with diversity antenna, optionally
	LAN	RJ45 10/100/1000 Mbps
Interfaces	Serial	1 x RS-232, COM 1 optionally 5 V
	USB	2 x USB
		1 x Service USB
Audio	speaker integrated	
Voice	Advantech-DLoG Voice Kit	speaker/mic via handset, optionally
Power Supply	DC	12/24 VDC or 24/48 VDC, galvanically isolated
		voltage sags up to 5 VDC can be handled for up to 20 sec
Environmental	IP protection class	IP 67 and IP 66 (contains IP 65 and IP 54)
	Certifications	CE/FCC Class B
		CCC China, BSMI / NCC Taiwan
		TELEC Japan
	Operating temperature	-30 to +50 °C / -22 to 122 °F
	Relative humidity	10 to 90% at 40 °C, non condensing
Shock/Vibration	Class 5M3 according DIN EN 60721-3-5 and MIL-STD 810F (US Highway Truck)	

Information in this document is subject to change without prior notice. The software and hardware designations used in this text are in most cases also registered trademarks and are thus subject to law.