



SPECIFICATIONS

FREQUENCY RANGE: 2.0 - 4.0 GHz
 COUPLING (INCLUDES FREQUENCY SENSITIVITY): 6 ± 1.00 dB
 FREQUENCY SENSITIVITY: ± 0.60 dB
 INSERTION LOSS: (EXCLUDING COUPLED POWER) 0.20 dB (TRUE) 1.80 dB
 DIRECTIVITY: 22 dB MINIMUM
 PRIMARY LINE: 1.15 VSWR MAX.
 SECONDARY LINE: 1.15 VSWR MAX.
 AVG. INCIDENT: 50 WATTS POWER
 AVG. REFLECTED: 2 WATTS POWER
 PEAK: 3 KW POWER



Pasternack Enterprises, Inc.
 P.O. Box 16759 | Irvine | CA | 92623

Phone: (949) 261-1920 | Fax: (949) 261-7451

Website: www.pasternack.com | E-Mail: sales@pasternack.com

DWG TITLE

PE2202-6

DES.

SMA FEMALE DIRECTIONAL COUPLER,
FREQUENCY RANGE: 2-4 GHz

REV. B

FSCM NO. 53919

CAD FILE 101012

SCALE N/A

SIZE A

2233

NOTES:

1. UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL.
2. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME.
3. DIMENSIONS ARE IN INCHES [mm].