


SAW Bandpass Filter 220002B



1. Features

- IF bandpass filter
- High attenuation
- Single-ended operation
- Dip Package
- Maximum Storage Temperature Range : -40°C ~ 85°C
- Electrostatics Sensitive Device (ESD)

2. Package Dimension



Package : D3512

Dimensions shown are nominal in millimeters
 Base : Fe(SPCC), Au plating over Ni plated
 Cap : Cu & Cr Alloy, Ni Plated
 Termination : Kovar, Au Plated

Pin Configuration	
1	Input
5	Output
2, 4	Ground
3, 6	Case ground

	ITF Co., Ltd. 102-901, Bucheon Technopark 364, Samjeong-Dong, Ojeong-Gu, Bucheon-City, Gyeonggi-Do, Korea 421-809	Part No.	220002B	
		Rev. Date	2008-11-11	
		Rev.	NW8028-CS01	1/5

SAW Bandpass Filter 220002B



3. Specifications

Fo = 62.6 MHz


Terminating source impedance : 50Ω and matching network

Terminating load impedance : 50Ω and matching network

		Minimum	Typical	Maximum
Center Frequency	MHz	-	62.6	-
Insertion Loss	dB	-	21.7	24.0
1dB Bandwidth	MHz	0.5	0.62	-
3dB Bandwidth	MHz	-	0.8	-
20dB Bandwidth	MHz	-	1.27	1.37
40dB Bandwidth	MHz	-	1.49	1.6
Amplitude Ripple (Fo +/- 0.225 MHz)	dB	-	0.35	0.9
Group Delay Variation (Fo +/- 0.225 MHz)	nsec	-	200	350
Absolute Delay	usec	-	4.05	-
Ultimate Rejection	dB	50	57	-
Temperature Coefficient of Frequency	ppm/°C ²	-	-0.03	-

Notes :

- 1) All specifications are based on the matching schematic shown below
- 2) All specifications are measured by Agilent Network analyzer and full 2 port calibration at room temperature
- 3) All attenuation measurements are measured relative to insertion loss


	ITF Co., Ltd. 102-901, Bucheon Technopark 364, Samjeong-Dong, Ojeong-Gu, Bucheon-City, Gyeonggi-Do, Korea 421-809	Part No.	220002B	
		Rev. Date	2008-11-11	
		Rev.	NW8028-CS01	2/5

SAW Bandpass Filter 220002B



4. Matching Schematic

(Actual matching values may vary due to PCB layout and parasitics)



$$L1 = L2 = 180\text{nH}$$

$$C1 = C2 = 56\text{ pF}$$


5. Marking Configuration

ITF¹⁾08A001²⁾

220002B³⁾

62.6⁴⁾-0.6M⁵⁾



- 1) Manufacturer name
- 2) Lot Number
- 3) Part Number
- 4) Center Frequency
- 5) 1dB-Bandwidth

	ITF Co., Ltd. 102-901, Bucheon Technopark 364, Samjeong-Dong, Ojeong-Gu, Bucheon-City, Gyeonggi-Do, Korea 421-809	Part No.	220002B	
		Rev. Date	2008-11-11	
		Rev.	NW8028-CS01	3/5

SAW Bandpass Filter 220002B



6. Typical Performance (at +25°C)







ITF Co., Ltd.
 102-901, Bucheon Technopark 364,
 Samjeong-Dong, Ojeong-Gu, Bucheon-City,
 Gyeonggi-Do, Korea 421-809

Part No. 220002B

Rev. Date 2008-11-11

Rev. NW8028-CS01 4/5

SAW Bandpass Filter 220002B



ITF Co., Ltd.
 102-901, Bucheon Technopark 364,
 Samjeong-Dong, Ojeong-Gu, Bucheon-City,
 Gyeonggi-Do, Korea 421-809

Part No.	220002B	
Rev. Date	2008-11-11	
Rev.	NW8028-CS01	5/5