



# DS9072/DS9075/DS9076

## SIP Stik Connectors

### Features

- ◆ Provides Snap-In Connection Between SIP Stiks and Motherboard
- ◆ Low Insertion Force, Redundant Contacts
- ◆ All Connectors are RoHS Compliant

### Ordering Information

PART	DESCRIPTION	LENGTH (in)	PITCH (in)	ORIGINAL MANUFACTURER PART # (FOR REFERENCE ONLY)
DS9072-40V	40 contact, vertical position	2.950	0.050	Molex 15-82-0782
DS9072H-40R	40 contact, high-profile right-angle position	2.950	0.050	Molex 15-82-1528
DS9072-72V	72 contact, vertical position	4.550	0.050	Molex 15-82-0772
DS9072H-72R	72 contact, high-profile right-angle position	4.550	0.050	Molex 15-82-0329
DS9072L-72R	72 contact, low-profile right-angle position	4.550	0.050	Molex 15-82-1303

### 40-Position DIP-to-SIP and SIP-to-DIP Adaptors for Development of DS2250 Micro Stik Products

PART	DESCRIPTION	PITCH (in)	ADAPTOR
DS9075-40V	40 contact, horizontal DIP plug with 40 contact, low-profile vertical position SIMM connector	0.050	SIP-to-DIP
DS9076-40	40 contact, vertical SIMM edge card with 40 contact, vertical DIP socket	0.050	DIP-to-SIP

SITE  
SEARCHPART  
SEARCH

WHAT'S NEW

PRODUCTS

SOLUTIONS

DESIGN

APPNOTES

SUPPORT

BUY

COMPANY

MEMBER

[Maxim](#) > [Products](#) > [Microcontrollers](#)

# DS9072, DS9075, DS9076

SIP Stik Connectors

[QuickView](#)[Technical Documents](#)[Ordering Info](#)[More Information](#)[All](#)

## Ordering Information

Notes:

1. Other options and links for purchasing parts are listed at: <http://www.maxim-ic.com/sales>.
2. [Didn't Find What You Need?](#) Ask our applications engineers. Expert assistance in finding parts, usually within one business day.
3. Part number suffixes: T or T&R = tape and reel; + = RoHS/lead-free; # = RoHS/lead-exempt. More: See [Full Data Sheet](#) or [Part Naming Conventions](#).
4. \* Some packages have variations, listed on the drawing. "PkgCode/Variation" tells which variation the product uses.

### Devices: 1-2 of 2

DS9072	Free Sample	Buy	Package: TYPE PINS FOOTPRINT DRAWING CODE/VAR *	Temp	RoHS/Lead-Free? Materials Analysis
DS9072-40V/NO-BRAND	<input type="checkbox"/>	<input type="checkbox"/>		0C to +70C	RoHS/Lead-Free: See data she
DS9072H-40R/NO-BRAND	<input type="checkbox"/>	<input type="checkbox"/>		0C to +70C	RoHS/Lead-Free: See data she

## Didn't Find What You Need?

- [Next Day Product Selection Assistance from Applications Engineers](#)
- [Parametric Search](#)
- [Applications Help](#)

### QuickView

Description  
[Key Features](#)  
 Applications/Uses  
 Key Specifications  
 Diagram

### Technical Documents

[Data Sheet](#)  
 Application Notes  
[Design Guides](#)  
 Engineering Journals  
[Reliability Reports](#)  
 Software/Models  
 Evaluation Kits

### Ordering Info

Price and Availability  
 Samples  
 Buy Online  
 Package Information  
 Lead-Free Information

### More Information

Related Products  
 Notes and Comments  
 Evaluation Kits

2007-06-01

This page last modified: 2007-06-01

[CONTACT US: SEND US AN EMAIL](#)