

N - CHANNEL ENHANCEMENT MODE
 POWER MOS TRANSISTORS

TYPE	V _{DSS}	R _{DS(on)}	I _D ■
IRF720	400 V	1.8 Ω	3.3 A
IRF720FI	400 V	1.8 Ω	2.5 A
IRF721	350 V	1.8 Ω	3.3 A
IRF721FI	350 V	1.8 Ω	2.5 A
IRF722	400 V	2.5 Ω	2.8 A
IRF722FI	400 V	2.5 Ω	2.0 A
IRF723	350 V	2.5 Ω	2.8 A
IRF723FI	350 V	2.5 Ω	2.0 A

- HIGH VOLTAGE - FOR OFF LINE APPLICATIONS
- ULTRA FAST SWITCHING
- EASY DRIVE - FOR REDUCED COST AND SIZE

INDUSTRIAL APPLICATIONS:

- ELECTRONIC LAMP BALLAST
- DC SWITCH


N - channel enhancement mode POWER MOS field effect transistors. Easy drive and very fast switching times make these POWER MOS transistors ideal for high speed switching applications. Applications include off-line use, constant current source, ultrasonic equipment and switching power supplies start-up circuits.

ABSOLUTE MAXIMUM RATINGS

 TO-220
 ISOWATT220

V _{DS} *	Drain-source voltage (V _{GS} = 0)				
V _{DGR} *	Drain-gate voltage (R _{GS} = 20 kΩ)				
V _{GS}	Gate-source voltage				
I _{DM} (•)	Drain current (pulsed)				
I _{DLM}	Drain inductive current, clamped (L = 100 μH)				
I _D	Drain current (cont.) at T _c = 25°C	400	350	400	350
I _D	Drain current (cont.) at T _c = 100°C	400	350	400	350
I _D ■	Drain current (cont.) at T _c = 25°C	13	13	11	11
I _D ■	Drain current (cont.) at T _c = 100°C	13	13	11	11
P _{tot} ■	Total dissipation at T _c < 25°C	720	721	722	723
P _{tot} ■	Derating factor	3.3	3.3	2.8	2.8
T _{stg}	Storage temperature	2.1	2.1	1.8	1.8
T _j	Max. operating junction temperature	720FI	721FI	722FI	723FI

TO-220 ISOWATT220

 INTERNAL SCHEMATIC
 DIAGRAM


* T = 25°C to 125°C

(•) Repetitive Rating: Pulse width limited by max junction temperature.

■ See note on ISOWATT220 on this datasheet.

THERMAL DATA

TO-220 | ISOWATT220

$R_{th(j-case)}$	Thermal resistance junction-case	max	2.50	4.16	$^{\circ}\text{C}/\text{W}$
$R_{th(c-s)}$	Thermal resistance case-sink	typ	0.5	$^{\circ}\text{C}/\text{W}$	$^{\circ}\text{C}/\text{W}$
$R_{th(j-amb)}$	Thermal resistance junction-ambient	max	80	$^{\circ}\text{C}/\text{W}$	$^{\circ}\text{C}/\text{W}$
T_I	Maximum lead temperature for soldering purpose		300		$^{\circ}\text{C}$

ELECTRICAL CHARACTERISTICS ($T_{case} = 25^{\circ}\text{C}$ unless otherwise specified)

Parameters	Test Conditions	Min.	Typ.	Max.	Unit
------------	-----------------	------	------	------	------

OFF

$V_{(BR)DSS}$	Drain-source breakdown voltage	$I_D = 250 \mu\text{A}$ for IRF720/722/720FI/722FI for IRF721/723/721FI/723FI	$V_{GS} = 0$	400			V
I_{DSS}	Zero gate voltage drain current ($V_{GS} = 0$)	$V_{DS} = \text{Max Rating}$ $V_{DS} = \text{Max Rating} \times 0.8$	$T_c = 125^{\circ}\text{C}$		250	μA	μA
I_{GSS}	Gate-body leakage current ($V_{DS} = 0$)	$V_{GS} = \pm 20 \text{ V}$			± 500	nA	

ON **

$V_{GS(\text{th})}$	Gate threshold voltage	$V_{DS} = V_{GS}$	$I_D = 250 \mu\text{A}$	2		4	V
$I_{D(on)}$	On-state drain current	$V_{DS} > I_{D(on)} \times R_{DS(on) \text{ max}}$ for IRF720/721/720FI/721FI for IRF722/723/722FI/723FI	$V_{GS} = 10 \text{ V}$	3.3			A
$R_{DS(on)}$	Static drain-source on resistance	$V_{GS} = 10 \text{ V}$ for IRF720/721/720FI/721FI for IRF722/723/722FI/723FI	$I_D = 1.8 \text{ A}$		1.8	Ω	Ω

DYNAMIC

g_{fs}^{**}	Forward transconductance	$V_{DS} > I_{D(on)} \times R_{DS(on) \text{ max}}$ $I_D = 1.8 \text{ A}$	1.0			mho
C_{iss} C_{oss} C_{rss}	Input capacitance Output capacitance Reverse transfer capacitance	$V_{DS} = 25 \text{ V}$ $V_{GS} = 0$	$f = 1 \text{ MHz}$		600 200 40	pF pF pF

SWITCHING

$t_d(\text{on})$ t_r	Turn-on time Rise time	$V_{DD} = 175 \text{ V}$ $R_i = 50 \Omega$	$I_D = 1.5 \text{ A}$		40 50	ns ns
	$t_d(\text{off})$ t_f		(see test circuit)		100 50	ns ns
Q_g	Total Gate Charge	$V_{GS} = 10 \text{ V}$ $V_{DS} = \text{Max Rating} \times 0.8$	$I_D = 3.3 \text{ A}$		15	nC

ELECTRICAL CHARACTERISTICS (Continued)

Parameters	Test Conditions	Min.	Typ.	Max.	Unit
------------	-----------------	------	------	------	------




SOURCE DRAIN DIODE

I_{SD} $I_{SDM} (*)$	Source-drain current Source-drain current (pulsed)			3.3 13	A A
V_{SD}	Forward on voltage	$I_{SD} = 3.3 \text{ A}$	$V_{GS} = 0$		1.6 V
t_{rr}	Reverse recovery time			450	ns
Q_{rr}	Reverse recovered charge	$I_{SD} = 3.3 \text{ A}$	$di/dt = 100 \text{ A}/\mu\text{s}$	3.1	μC


** Pulsed: Pulse duration $\leq 300 \mu\text{s}$, duty cycle $\leq 1.5\%$

(*) Repetitive Rating: Pulse width limited by max junction temperature


■ See note on ISOWATT220 in this datasheet

Safe operating areas
(standard package)Thermal impedance
(standard package)Derating curve
(standard package)


Output characteristics




Output characteristics




Transfer characteristics




Transconductance




Static drain-source on resistance




Maximum drain current vs temperature




Gate charge vs gate-source voltage




Capacitance variation




Normalized breakdown voltage vs temperature




Normalized on resistance vs temperature



Source-drain diode forward characteristics




Clamped inductive test circuit




SC-0242

Clamped inductive waveforms




SC-0243

Switching times test circuit



SC-0246

Gate charge test circuit



SC-0244

ISOWATT220 PACKAGE CHARACTERISTICS AND APPLICATION.

ISOWATT220 is fully isolated to 2000V dc. Its thermal impedance, given in the data sheet, is optimised to give efficient thermal conduction together with excellent electrical isolation.

The structure of the case ensures optimum distances between the pins and heatsink. The ISOWATT220 package eliminates the need for external isolation so reducing fixing hardware. Accurate moulding techniques used in manufacture assure consistent heat spreader-to-heatsink capacitance.

ISOWATT220 thermal performance is better than that of the standard part, mounted with a 0.1mm mica washer. The thermally conductive plastic has a higher breakdown rating and is less fragile than mica or plastic sheets. Power derating for ISOWATT220 packages is determined by:


$$P_D = \frac{T_j - T_c}{R_{th}}$$

from this I_{Dmax} for the POWER MOS can be calculated:


$$I_{Dmax} \leq \sqrt{\frac{P_D}{R_{DS(on)} \text{ (at } 150^\circ\text{C)}}}$$

ISOWATT DATA


Safe operating areas



Thermal impedance



Derating curve



THERMAL IMPEDANCE OF ISOWATT220 PACKAGE

Fig. 1 illustrates the elements contributing to the thermal resistance of transistor heatsink assembly, using ISOWATT220 package.

The total thermal resistance $R_{th(\text{tot})}$ is the sum of each of these elements.

The transient thermal impedance, Z_{th} for different pulse durations can be estimated as follows:

1 - for a short duration power pulse less than 1ms;

$$Z_{th} < R_{thJ-C}$$

2 - for an intermediate power pulse of 5ms to 50ms:

$$Z_{th} = R_{thJ-C}$$

3 - for long power pulses of the order of 500ms or greater:

$$Z_{th} = R_{thJ-C} + R_{thC-HS} + R_{thHS-amb}$$

It is often possible to discern these areas on transient thermal impedance curves.

Fig. 1

$$R_{thJ-C} \quad R_{thC-HS} \quad R_{thHS-amb}$$