

# VOLTAGE CONTROLLED OSCILLATOR

**TOM9305**  
200 - 400 MHz

## Available as:

- TOM9305, 4 Pin TO-8 (T4)
- TON9305, 4 Pin Surface Mount (SM3)
- TOP9305, 4 Pin Flatpack (FP4)
- BXO9305, Connectorized Housing (H1)

## Features

- Low Noise Bipolar Transistor
- Broad Tuning Range
- Operating Case Temp. -55 °C to + 85 °C
- Environmental Screening Available

## Specifications



CHARACTERISTIC	TYPICAL Ta = +25°C	MIN/MAX Ta = -55°C to +85 °C
Frequency	200 - 400 MHz	200 - 400 MHz
Output Power (dBm)	+12.5	+10.0 Min.
Power Flatness (dB)	±0.4	±1.0 Max.
Tuning Voltage Range (v)	1 to 19	0 to 20
Tuning Voltage Sensitivity (MHz/V)	20	5.0 Min.
Harmonics (dBc)	-30	-17 Max.
Spurious (dBc)	<-80	-80 Max.
3dB Modulation BW, Zg = 50 Ohms	---	3 MHz Min.
Pushing (MHz/V)	1.0	2.0 Max.
Pulling (MHz); 12 dB RL	4	9.0 Max.
Frequency Drift (MHz/°C)	---	0.1 Max.
Power	Vdc mA	+15 14
		+15 18 Max.

## Maximum Ratings


Ambient Operating Temperature ..... -55°C to + 100 °C  
 Storage Temperature ..... -62°C to + 125 °C  
 Case Temperature ..... + 125 °C  
 DC Voltage ..... + 20 Volts  
 Maximum DC Tuning Voltage ..... + 20 Volts  
 Minimum DC Tuning Voltage ..... 0 Volt

Note: Care should always be taken to effectively ground the case of each unit.

## Typical Performance Data



Legend ——— +25 °C - - - - +85 °C - - - - -55 °C



### Notes:

1. Phase Noise is measured using the Aeroflex PN9000.
2. Worst case phase noise @ 100KHz offset across frequency range and temperature extremes is -120dBc/Hz.



Spectrum Microwave · 2144 Franklin Drive N.E. · Palm Bay, Florida 32905 · PH (888) 553-7531 · Fax (888) 553-7532 05/15/05

www.SpectrumMicrowave.com Spectrum Microwave (Europe) · 2707 Black Lake Place · Philadelphia, Pa. 19154 · PH (215) 464-4000 · Fax (215) 464-4001