

## 15 Amp Vertical Rackmount Surge Strip



### Features

- Designed to have a low-profile our strips are just 1 5/8" wide by 1 3/8" high.
- Constructed of rugged light weight aluminum.
- Designed for a variety of applications:
  - Install in your server cabinets
  - Wall mount cabinets
  - Open frame racks
  - Or install horizontally above your work bench.
- Each outlet strip included a hardware mounting kit. Order P/N: [1585CLIP](#) for additional hardware kit.
- Receptacles are 1" square and are equally spaced over the length of the power strip.
- With on/off switch or pilot light and 15 Amp circuit breaker.
- Plug type available is a NEMA 5-15P straight blade.
- [Click here for our non-surge protected version.](#)

### Surge Features

- Rated 15 amps, 120 volts.
- Heavy duty 14 gauge wire cord - 14/3 SJT type for extreme temperature ranges and integral molded plug.
- 18,000 Amp rated MOV's & filter capacitor provide surge suppression and EMI/RFI noise protection
- Maximum 54,000 Amps transient current and 780 Joules
- 400V UL 1449 rating
- Protection in all 3 AC modes (L-N, L-G, N-G)
- Voltage suppression at the outlet guards against transients from equipment on the outlet strip
- Green indicator light confirms surge module is active
- Internal protection will disconnect the surge module at the end of it's useful life (and extinguish the green light) but will maintain power to the load, now unprotected.
- CSA certified, Standards C22.2 (No. 21-95, No. 42-99 and No. 8-M1986)
- UL listed, Standards UL1363, UL1283 and UL1449.

### Accessoires

Part No. On-Off Switch	Part No. Pilot Light	Strip Length	Number of Outlets	Surge Protected	Cord Length (ft)	Color	NEMA Plug Type
1585H8A1S	1585T8A1S	48.00	8	Yes	6	Natural	5-15P
1585H8B1S	1585T8B1S	48.00	8	Yes	15	Natural	5-15P
1585H10A1S	1585T10A1S	48.00	10	Yes	6	Natural	5-15P
1585H10B1S	1585T10B1S	48.00	10	Yes	15	Natural	5-15P

<b>1585H15A1S</b>	<b>1585T15A1S</b>	48.00	15	Yes	6	Natural	5-15P
<b>1585H15B1S</b>	<b>1585T15B1S</b>	48.00	15	Yes	15	Natural	5-15P
<b>1587H11A1S</b>	<b>1587T11A1S</b>	70.00	11	Yes	6	Natural	5-15P
<b>1587H11B1S</b>	<b>1587T11B1S</b>	70.00	11	Yes	15	Natural	5-15P
<b>1587H19A1S</b>	<b>1587T19A1S</b>	70.00	19	Yes	6	Natural	5-15P
<b>1587H19B1S</b>	<b>1587T19B1S</b>	70.00	19	Yes	15	Natural	5-15P
<b>1588H12A1S</b>	<b>1588T12A1S</b>	77.00	12	Yes	6	Natural	5-15P
<b>1588H12B1S</b>	<b>1588T12B1S</b>	77.00	12	Yes	15	Natural	5-15P

*Les données sont sujettes à changement sans préavis.*

© 2014. Hammond Manufacturing Ltd. Tous droits réservés.