

SEARCH

PART # DOC SITE

Display Overview

Product Lineup

3.5" Lineup

5.5" Lineup

6.3" Lineup

6.5" Lineup

7.0" Lineup

8.4" Lineup

NL10276BC16-01

**NL6448BC26-08D**

NL6448BC26-09

NL6448BC26-09C

NL8060BC21-02

NL8060BC21-03

NL8060BC21-04

NL8060BC21-06

9.0" Lineup

10.4" Lineup

12.1" Lineup

15.0" Lineup

15.3" Lineup

19.0" Lineup

20.1" Lineup

21.3" Lineup

22.5" Lineup

Industrial TFT

Transflective TFT

Markets

Support

LCD Product Brief

NL6448BC26-08D

8.4 inches (21 cm) VGA for industrial applications  
UA-SFT

Characteristics	
Model number	NL6448BC26-08D
Drive method	a-Si TFT active matrix
Screen size	8.4 inches (21 cm diagonal)
Number of pixels	640 x 480
Effective display area	170.88 (H) x 128.16 (V) mm
Backlight	One side 2 CCFL
Luminance	400 cd/m <sup>2</sup>
Contrast	800:1
Display colors	16.77M colors (8bit) / 262K colors (6bit)
Viewing angle	Up: 85°, down: 85°, right: 85°, left: 85° [1]
Response time (t <sub>on</sub> )	20 ms [2]
Outline dimension	200.0 (W) x 152.0 (H) x 10.5 (D) mm
Weight	330 g
Operating temperature	-10°C to +70°C
Storage temperature	-20°C to +80°C
Power supply voltage	3.3V
Power consumption	5.4 W [3]
Input signal	LVDS (RGB 8 bits each / 6 bits each)
Remark	-

Note:

[1] Contrast of 10:1 or higher

[2] Value of Ton+Toff (0% ? 90%)

[3] Value does not include power consumption of recommended inverter

All values are typical values.

All specifications shown on this web site are subject to change without notice.

CONTACT US PRINT

FEATURE

FFF-Compatibility

Super Fine Technology