



1 dB Fixed Attenuator, BNC Male To BNC Female Rated To 1 Watt Up To 2 GHz

TECHNICAL DATA SHEET

PE7000-1

**1 dB Fixed Attenuator, BNC Male To BNC Female Rated To 1 Watt Up To 2 GHz**

**Configuration**

Design	Fixed, Bidirectional Attenuator
Connector 1	BNC Male
Connector 2	BNC Female
Body Material and Plating	Brass, Nickel

**Electrical Specifications**

Frequency Range, GHz	DC to 2
Impedance, Ohms	50
Attenuation Value, dB	1
Maximum Input Power, Watts	1
Maximum VSWR	1.2:1

**Frequency 1**

Range, GHz	DC to 2
Attenuation Accuracy, dB	± 0.3

**Mechanical Specifications**

**Temperature**

Operating Range, deg C	-30 to +70
------------------------	------------

**Size**

Length, in [mm]	1.8 [45.72]
Width, in [mm]	0.57 [14.48]

**Connector 1**

Type	BNC Male
Contact Material and Plating	Brass, Gold
Coupling Nut Material and Plating	Brass, Nickel
Body Material and Plating	Brass, Nickel

**Connector 2**

Type	BNC Female
Contact Material and Plating	Beryllium Copper, Gold
Body Material and Plating	Brass, Nickel

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [1 dB Fixed Attenuator, BNC Male To BNC Female Rated To 1 Watt Up To 2 GHz PE7000-1](#)

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.





1 dB Fixed Attenuator, BNC Male To BNC  
Female Rated To 1 Watt Up To 2 GHz

TECHNICAL DATA SHEET

PE7000-1

**Compliance Certifications** (visit [www.Pasternack.com](http://www.Pasternack.com) for current document)

**Plotted and Other Data**

Notes:

Values at 25 °C, sea level

1 dB Fixed Attenuator, BNC Male To BNC Female Rated To 1 Watt Up To 2 GHz from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and fiber optic products maintain a 99% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [1 dB Fixed Attenuator, BNC Male To BNC Female Rated To 1 Watt Up To 2 GHz PE7000-1](#)


URL: <http://www.pasternack.com/1db-fixed-bnc-female-bnc-male-1-watt-attenuator-pe7000-1-p.aspx>

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.

# PE7000-1 CAD Drawing

1 dB Fixed Attenuator, BNC Male To BNC Female Rated To 1 Watt Up To 2 GHz

P/N	ATTEN.	FIGURE
PE7000-1	1 dB	1
PE7000-2	2 dB	1
PE7000-3	3 dB	1
PE7000-6	6 dB	1
PE7000-10	10 dB	1
PE7000-20	20 dB	1
PE7000-30	30 dB	1



**BNC MALE**

**BNC FEMALE**

**FIGURE 1**

NOTES:  
 1. UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL.  
 2. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME.  
 3. DIMENSIONS ARE IN INCHES [mm].

DWG TITLE  
**PE7000**

FSCM NO. 53919

CAD FILE 011513

SCALE N/A

SIZE A

2233

**PE PASTERNAK®**  
 Pasternack Enterprises, Inc.  
 P.O. Box 16759 | Irvine | CA | 92623  
**Phone:** (949) 261-1920 | **Fax:** (949) 261-7451  
**Website:** www.pasternack.com | **E-Mail:** sales@pasternack.com