



SPN1014

N-Channel Enhancement Mode MOSFET

DESCRIPTION

The SPN1014 is the N-Channel enhancement mode power field effect transistors are produced using high cell density , DMOS trench technology. This high density process is especially tailored to minimize on-state resistance and provide superior switching performance. These devices are particularly suited for low voltage applications such as notebook computer power management and other battery powered circuits where high-side switching , low in-line power loss, and resistance to transients are needed.



APPLICATIONS

- Drivers : Relays/Solenoids/Lamps/Hammers
- Power Supply Converter Circuits
- Load/Power Switching Cell Phones, Pagers


FEATURES

- ◆ N-Channel
20V/0.65A,RDS(ON)=380mΩ@VGS=4.5V
20V/0.55A,RDS(ON)=450mΩ@VGS=2.5V
20V/0.45A,RDS(ON)=800mΩ@VGS=1.8V
- ◆ Super high density cell design for extremely low RDS (ON)
- ◆ Exceptional on-resistance and maximum DC current capability
- ◆ SOT-523 (SC-89) package design

PIN CONFIGURATION(SOT-523 / SC-89)



PART MARKING



Y : year
W: week



SPN1014

N-Channel Enhancement Mode MOSFET

PIN DESCRIPTION

Pin	Symbol	Description
1	G	Gate
2	S	Source
3	D	Drain

ORDERING INFORMATION

Part Number	Package	Part Marking
SPN1014S52RG	SOT-523	4X
SPN1014S52RGB	SOT-523	4X

- ※ SPN1014S52RG : Tape Reel ; Pb – Free
- ※ SPN1014S52RGB : Tape Reel ; Pb – Free, Halogen – Free

ABSOLUTE MAXIMUM RATINGS

(TA=25°C Unless otherwise noted)

Parameter	Symbol	Typical	Unit
Drain-Source Voltage	V _{DSS}	20	V
Gate –Source Voltage	V _{GSS}	±12	V
Continuous Drain Current(T _J =150°C)	T _A =25°C	ID	0.65
	T _A =80°C		0.45
Pulsed Drain Current	I _{DM}	1.0	A
Continuous Source Current(Diode Conduction)	I _S	0.3	A
Power Dissipation	T _A =25°C	P _D	0.27
	T _A =70°C		0.16
Operating Junction Temperature	T _J	-55/150	°C
Storage Temperature Range	T _{STG}	-55/150	°C



SPN1014

N-Channel Enhancement Mode MOSFET

ELECTRICAL CHARACTERISTICS

(TA=25°C Unless otherwise noted)





Parameter	Symbol	Conditions	Min.	Typ	Max.	Unit
Static						
Drain-Source Breakdown Voltage	V _{(BR)DSS}	V _{GS} =0V, ID= 250uA	20			V
Gate Threshold Voltage	V _{GS(th)}	V _{DS} =V _{GS} , ID=250uA	0.35		1.0	
Gate Leakage Current	I _{GSS}	V _{DS} =0V, V _{GS} =±12V			30	uA
Zero Gate Voltage Drain Current	I _{DSS}	V _{DS} = 16V, V _{GS} =0V			1	
		V _{DS} = 16V, V _{GS} =0V T _J =55°C			5	uA
On-State Drain Current	I _{D(on)}	V _{DS} ≥ 4.5V, V _{GS} =5V	0.7			A
Drain-Source On-Resistance	R _{DSS(on)}	V _{GS} =4.5V, ID=0.65A		0.26	0.38	
		V _{GS} =2.5V, ID=0.55A		0.32	0.45	
		V _{GS} =1.8V, ID=0.45A		0.42	0.80	
Forward Transconductance	g _{fs}	V _{DS} =10V, ID=0.4A		1.0		S
Diode Forward Voltage	V _{SD}	I _S =0.15A, V _{GS} =0V		0.8	1.2	V
Dynamic						
Total Gate Charge	Q _g	V _{DS} =10V, V _{GS} =4.5V, ID=0.6A		1.2	1.5	
Gate-Source Charge	Q _{gs}			0.2		nC
Gate-Drain Charge	Q _{gd}			0.3		
Turn-On Time	t _{d(on)}	V _{DD} =10V, R _L =10Ω , ID=0.5A V _{GEN} =4.5V , R _G =6Ω		5	10	
	t _r			8	15	
Turn-Off Time	t _{d(off)}			10	18	
	t _f			1.2	2.8	ns



SPN1014

N-Channel Enhancement Mode MOSFET

TYPICAL CHARACTERISTICS









SPN1014

N-Channel Enhancement Mode MOSFET

TYPICAL CHARACTERISTICS








SPN1014

N-Channel Enhancement Mode MOSFET

TYPICAL CHARACTERISTICS






SPN1014

N-Channel Enhancement Mode MOSFET

SOT-523 PACKAGE OUTLINE



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min	Max	Min	Max
A	0.700	0.900	0.028	0.035
A1	0.000	0.100	0.000	0.004
A2	0.700	0.800	0.028	0.031
b1	0.150	0.250	0.006	0.010
b2	0.250	0.325	0.010	0.013
c	0.100	0.200	0.004	0.008
D	1.500	1.700	0.059	0.067
E	0.750	0.850	0.030	0.033
E1	1.450	1.750	0.057	0.069
e	0.500 TYP		0.020 TYP	
e1	0.900	1.100	0.035	0.043
L	0.550 REF		0.022 REF	
L1	0.280	0.440	0.011	0.017
θ	0°	4°	0°	4°



SPN1014

N-Channel Enhancement Mode MOSFET

Information provided is alleged to be exact and consistent. SYNC Power Corporation presumes no responsibility for the penalties of use of such information or for any violation of patents or other rights of third parties which may result from its use. No license is granted by allegation or otherwise under any patent or patent rights of SYNC Power Corporation. Conditions mentioned in this publication are subject to change without notice. This publication surpasses and replaces all information previously supplied. SYNC Power Corporation products are not authorized for use as critical components in life support devices or systems without express written approval of SYNC Power Corporation.

©The SYNC Power logo is a registered trademark of SYNC Power Corporation
©2004 SYNC Power Corporation – Printed in Taiwan – All Rights Reserved
SYNC Power Corporation
7F-2, No.3-1, Park Street
NanKang District (NKSP), Taipei, Taiwan 115
Phone: 886-2-2655-8178
Fax: 886-2-2655-8468
©<http://www.syncpower.com>
