



REV A January 2011

Oscilent Controlled Document

Ordering Code / Part Number	Product Description
821-IF80.0M-30B	80.0 MHz IF SAW Filter 29.95 MHz Bandwidth

Specification Contents

- o Mechanical Dimensions
- o Test Circuit
- o Maximum Ratings
- o Electrical Specification
- o Frequency Response
- o Smith Chart
- o VSWR

Notes

- o Electrostatic Sensitive Device (ESD) 
- o Avoid excessive ultrasonic exposure
- o Solderability compatible with JEDEC J-STD-020C Pb-free process, 260°C peak reflow temperature
- o This product complies with EU directive 2002/95/EC (RoHS compliance)






Mechanical Dimensions (mm)



Pin Description	
A, B, C, D, F, G, H, I	Ground
J	Input
E	Output

Test Circuit



Test Fixture & Values	
Input	L1=100 nH, C1=2.2 pF
Output	L2=100 nH
Source/Load Impedance	50 Ω

**Maximum Ratings**

Parameters Description	Unit	Minimum	Typical	Maximum
Operating Temperature Range	°C	-	25	-
Storage Temperature Range	°C	-40	-	85
Maximum DC Voltage	V	-	-	10
Maximum Input Power	dBm	-	-	10
Source Impedance (single ended) ⁽¹⁾	Ω	-	50	-
Load Impedance (single ended) ⁽¹⁾	Ω	-	50	-

Notes: With Matching Network (Ref. Testing Environment Circuit as shown above).

Those impedances could be modified with different impedance values and/or structures, if necessary.


Electrical Specification

Parameters Description	Unit	Minimum	Typical	Maximum
Center Frequency (Fo)	MHz	-	80.0	-
Insertion Loss at Fo	dB	-	27.4	29.0
Group Delay Variation (Fo±14.32MHz)	ns	-	32	50
Absolute Delay	us	-	2.24	-
Passband Ripple (Fo±14.32MHz)	dB	-	0.67	1.00
Bandwidth at -1dB	MHz	-	29.95	-
Bandwidth at -3dB	MHz	30	30.22	-
Bandwidth at -25dB	MHz	-	31.17	-
Bandwidth at -40dB	MHz	-	31.44	-
Ultimate Rejection	dB	48	50	-
Temperature Coefficient of Frequency	ppm/°C	-	-72	-




Frequency Response


Bandwidth at -1.0 dB




Bandwidth at -3.0 dB



Bandwidth at -25.0 dB




Bandwidth at -40.0 dB







Ripple Variation Fo±14.32MHz



Group Delay Variation Fo±14.32MHz



Smith Chart





VSWR

