



SPECIFICATIONS

FREQUENCY RANGE: 2 TO 4 GHz
 ISOLATION: 18
 LOSS (dB) MIN: 0.6
 VSWR MAX: 1.30:1
 FORWARD POWER: 10 WATT
 REVERSE POWER: 10 WATT
 INPUT CONNECTOR: N TYPE
 OUTPUT CONNECTOR: N TYPE



PASTERNAK ENTERPRISES, INC.
 P.O BOX 16759, IRVINE, CA 92623
 PHONE (949) 261-1920 FAX (949) 261-7451
 WEB ADDRESS: www.pasternack.com
 E-MAIL ADDRESS: sales@pasternack.com
COAXIAL & FIBER OPTICS

DWG TITLE

PE8411

DES. N FEMALE CIRCULATOR, 2 - 4 GHz, 10W

REV. B

FSCM NO. 53919

CAD FILE 011712

SCALE N/A

SIZE A 2233

NOTES:

1. UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL.
2. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME.
3. DIMENSIONS ARE IN INCHES [mm].
4. LENGTH TOLERANCE IS $\pm 1.5\%$ OR $\pm 3/8"$, WHICHEVER IS GREATER.