


D3406 Product Details



D3406



Communications / Signal PC Board Relays



[Converted to EU RoHS/ELV Compliant \(Statement of Compliance\)](#)

Product Highlights:

- D34 / FT Relay Series
- DC Actuating System
- Input Voltage = 12 VDC
- Contact Arrangement = 2 Form C, DPDT, 2 C/O
- Contact Current Rating = 1.25 Amps.

[View all Features](#) | [Find Similar Products](#)

[Previous 1 ... 11 12 \[13\] 14 15 ... 20 Next](#)

Quick Links

- [Check Pricing & Availability](#)
- [Search for Tooling](#)
- [Product Feature Selector](#)
- [Compare Products](#)
- [Contact Us About This Product](#)

Documentation & Additional Information

Product Drawings:

- None Available

Catalog Pages/Data Sheets:

- [AXICOM Telecom, Signal and RF Relays](#) (PDF, English)

Product Specifications:

- [FT/FU Relay Datasheet](#) (PDF, English)

Application Specifications:

- None Available

Instruction Sheets:

- None Available

CAD Files:

- None Available

Additional Information:

- [Product Line Information](#)

Related Products:

- [Tooling](#)

[List all Documents](#)

Product Features (Please use the Product Drawing for all design activity)

Product Type Features:

- Termination Type = Through Hole

Electrical Characteristics:

- Actuating System = DC
- Input Voltage (VDC) = 12
- Contact Current Rating (Amps.) = 1.25
- [Coil Resistance \(?\)](#) = 480
- Coil Power, Nominal (mW) = 300
- Dielectric Between Coil and Contacts (V rms) = 1800

Body Related Features:

- [Series](#) = D34 / FT Relay
- Polarized = No

Contact Related Features:

- Mounting Options = PC Board
- Enclosure = Immersion Cleanable
- [FCC Part 68 Isolation](#) = Yes
- Approved Standards = CECC Approved, CSA Certified, IEC 60950, UL Recognized, UL1950
- Contact Material = Silver Nickel, Gold Overlay
- Approx. Dimensions (L x W x H) (mm [in]) = 15.00 x 7.50 x 10.00 [.591 x .296 x .394]
- Option = Bellecore GR1089
- DIP Package Style = Vertical
- Contact Type = Bifurcated
- Pin Configuration = DIP

Configuration Related Features:

- [Contact Arrangement](#) = 2 Form C, DPDT, 2 C/O
- [Coil Magnetic System](#) = Non Polarized, Monostable
- Coil Suppression Diode = Without

Industry Standards:

- [RoHS/ELV Compliance](#) = RoHS compliant, ELV compliant
- [Lead Free Solder Processes](#) = Wave solder capable to 240C, Wave solder capable to 260C, Wave solder capable to 265C
- RoHS/ELV Compliance History = Converted to comply with RoHS directive

Other:

- Brand = Axicom

