
NLT Technologies, Ltd. - Exclusive Representative





White LED backlights have been used in small (5-inch and smaller) consumer display products such as cell phones, portable media players and handheld global positioning systems for some time. As more efficient and more cost-effective white LEDs have become available, their use has spread to both small- and medium-size (up to about 15-inch) display products in a variety of applications, including test and measurement equipment, portable medical devices and other battery-powered products where power consumption must be minimized.

6.5-inch LCD module equipped with white LED backlight system



At a time when customers are moving away from cumbersome stationary display equipment toward products that are more portable and often batteryoperated, the focus of designers has shifted to equipment that reduces power consumption, conserves energy, and allows for modularization while protecting the environment. In the context of these trends, LED-based LCDs offer distinct advantages over their CCFL counterparts.

- > Low voltage
- > Low EMI
- > No need for an inverter
- > Reduced power consumption
- > Reduced module thickness and weight
- > High reliability
- > Lower risk of damage due to shock and vibration
- > Mercury-free and therefore more environmentally friendly than CCFL products

LED Backlight LCDs

on	Part Number	Additional Attributes	Availability
bout our	3.5-inch to 4.3-inch LED d	isplays are available in the Industrial Mobile I	Display flyer.
NL6448BC18-01 400 cd/m ² , CR 85	400 cd/m², CR 850:1, 6-bit digital RGB	Now	
	NL6448BC18-01F	800 cd/m², CR 850:1, 6-bit digital RGB	NOW
GA	NL6448BC18-06F	800 cd/m², CR 850:1, 6-bit digital RGB, portrait	Now
	NL6448BC18-07	280 cd/m², CR 850:1, 6-bit digital RGB	Now
C A	NL6448BC20-21C	800 cd/m ² , CR 600:1, ST-NLT, LVDS	Now
GA	NL6448BC20-21D	550 cd/m ² , CR 600:1, LVDS	
G		NL6448BC18-01 NL6448BC18-01F NL6448BC18-06F NL6448BC18-07 NL6448BC20-21C	NL6448BC18-01F 800 cd/m², CR 850:1, 6-bit digital RGB iA NL6448BC18-06F 800 cd/m², CR 850:1, 6-bit digital RGB, portrait NL6448BC18-07 280 cd/m², CR 850:1, 6-bit digital RGB NL6448BC20-21C 800 cd/m², CR 600:1, ST-NLT, LVDS

www.am.renesas.com/prod/displays www.nlt-technologies.co.jp/en

NLT Technologies, Ltd.

ENVIRONMENTAL INITIATIVES

Our products are RoHS compliant

Out of concern for the environment, NLT Technologies began reducing the use of hazardous substances in our LCD modules prior to the RoHS Directive. We have eliminated the six substances targeted in the RoHS Directive as well as other substances we have identified as potentially hazardous so that our products are now RoHS-compliant.

Renesas Electronics America Inc. 2880 Scott Boulevard Santa Clara, CA 95050-2554 1-408-588-6000 www.am.renesas.com/prod/displays

NLT Technologies, Ltd. 1753 Shimonumabe, Nakahara-Ku Kawasaki, Kanagawa 211-8666, Japan 044-435-1666 www.nlt-technologies.co.jp/en

NEC LCD Technologies, Ltd. New name Same company Same support Technologies, Ltd. As of July 1, 2011, NEC LCD Technologies, Ltd.
--

Renesas Electronics America Inc. is the exclusive representative of NLT Technologies in the Americas.

Note:

LED Backlight LCDs

Resolu-**Additional Attributes** Part Number Availability tion NL6448BC20-30/30D 600 cd/m², CR 600:1, 6/8-bit LVDS NL6448BC20-30C 900 cd/m², CR 600:1, ST-NLT, 6/8-bit LVDS NL6448BC20-30F 900 cd/m², CR 600:1, 6/8-bit LVDS VGA NL6448BC20-35/35D 600 cd/m², CR 800:1, 6-bit digital 1000 cd/m², CR 800:1, ST-NLT, 6.5" Now NL6448BC20-35C 6-bit digital NL6448BC20-35F 1000 cd/m², CR 800:1, 6-bit digital NL10276BC13-01 500 cd/m², CR 500:1, 6/8-bit digital RGB XGA 650 cd/m², CR 500:1, ST-NLT, NL10276BC13-01C 6/8-bit digital RGB NL8048BC19-02 400 cd/m², CR 1000:1, LVDS WQVGA NL8048BC19-02C 7.0" 550 cd/m², CR 800:1, ST-NLT, LVDS Now NL8048BC19-03 400 cd/m², CR 1000:1, LVDS, portrait 800 cd/m², CR 1000:1, NL6448BC26-20F 6-bit digital RGB, portrait Now NI 6448BC 26-22F 800 cd/m², CR 1000:1, 6-bit digital RGB NL6448BC26-26/26D 450 cd/m², CR 800:1, 6-bit digital VGA 900 cd/m², CR 800:1, ST-NLT, 6-bit digital NL6448BC26-26C Now 8.4" NL6448BC26-26F 900 cd/m², CR 800:1, 6-bit digital NL8060BC21-11/11D 400 cd/m², CR 800:1, LVDS SVGA NL8060BC21-11C 800 cd/m², CR 800:1, ST-NLT Now VGA NL8060BC21-11F 800 cd/m², CR 800:1, LVDS 8.9" WSVGA NL10260BC19-01D 300 cd/m², CR 700:1, LVDS, UA-SFT Now 9.0" **WVGA** NL8048BC24-09/09D 400 cd/m², CR 800:1, LVDS, UA-SFT Now NL6448BC33-70/70D 450 cd/m², CR 900:1, 6-bit digital RGB 900 cd/m², CR 900:1, ST-NLT, VGA NL6448BC33-70C 6-bit digital RGB NL6448BC33-70F 900 cd/m², CR 900:1, 6-bit digital RGB NL8060BC26-35/35D 400 cd/m², CR 900:1, LVDS SVGA NL8060BC26-35C $800\ cd/m^2$, CR 900:1, ST-NLT , LVDS Now 10.4" NL8060BC26-35F 800 cd/m², CR 900:1, LVDS 175 cd/m², CR 150:1, NL10276BC20-10 SR-NLT, 35% RR, LVDS NL10276BC20-12 150 cd/m², CR 400:1, LVDS XGA NL10276BC20-18/18D 400 cd/m², CR 900:1, LVDS NL10276BC20-18C 750 cd/m², CR 900:1, ST-NLT Q4 CY2011 NL10276BC20-18F 750 cd/m², CR 900:1, LVDS NL8060BC31-47/47D 450 cd/m², CR 900:1, LVDS SVGA NL8060BC31-50F 800 cd/m², CR 800:1, 6-bit digital RGB 12.1" NL10276BC24-19D 650 cd/m², CR 600:1, LVDS Now XGA NL10276BC24-21 450 cd/m², CR 900:1, LVDS WXGA NL12880BC20-05/05D 400 cd/m², CR 900:1, LVDS 400 cd/m², CR 600:1, LVDS, PSWG 15.0" XGA NL10276BC30-34D Now

Renesas Electronics America Inc. | 2880 Scott Boulevard, Santa Clara, CA 95050-2554 | Phone: 1 (408) 588-6000 | www.am.renesas.com

© 2011 Renesas Electronics America Inc. (REA). All rights reserved. All trademarks are the property of their respective owners. REA believes the information herein was accurate when given but assumes no risk as to its quality or use. All information is provided "as-is" without warranties of any kind, whether express, implied, statutory, or arising from course of dealing, usage, or trade practice, including without limitation as to merchantability, fitness for a particular purpose, or non-infringement. REA shall not be liable for any direct, indirect, special, consequential, incidental, or other damages whatsoever, arising from use of or reliance on the information herein, even if advised of the possibility of such damages. REA reserves the right, without notice, to discontinue products or make changes to the design or specifications of its products or other information herein, all contents are protected by U.S. and international copyright laws. Except as specifically permitted herein, no portion of this material may be reproduced in any form, or by any means, without prior written permission from Renesas Electronics America Incc.



LED Backlight LCDs

Continued from front page

Printed on Recycled Paper. Document No. 51070-6

