

Type Number	I_C Max Amps.	V_{CE0} @ I_C V @ A	V_{CBO} @ I_{CBO} V @ ma	h_{FE} @ I_C A	V_{EBO} @ I_{EBO} V @ ma	$V_{CE(sat)}$ @ I_C V @ A	V_{BE} V	f_{ac} KHz	Thermal Res. °C/W
-------------	-----------------	-------------------------	------------------------------	--------------------	------------------------------	-----------------------------	------------	--------------	-------------------

15-25 AMP TO-3 (except Emitter Pin Dia. .038 to .063) HIGH POWER

DTG-110B	25	40	5	90	20	65/300	1.0	2.0	100	0.5	5.0	.33	850	.08
DTG-600	25	50	5	75	20	50/	5.0	1.0	100	0.75	25.0	1.4	850	1.0
DTG-601	25	60	5	75	20	50/	5.0	1.0	100	0.75	25.0	1.4	850	1.0
DTG-602	25	70	5	90	20	50/	5.0	1.0	100	0.75	25.0	1.4	850	1.0
DTG-603	25	80	5	90	20	50/	5.0	1.0	100	0.75	25.0	1.4	850	1.0
DTG-1010	15	110	5	325	10			1.0	200	0.5	12	1.0	250	0.8
DTG-1110	15	80	8	200	15			1.0	100	0.5	10	1.0	450	0.8
DTG-1200	15	120	8	120	10	22.5/	8.0	1.0	200	0.5	12	1.0	250	0.8
DTG-2000	25	30	8	60	10	25	8.0	1.0	200	0.9	25	1.0	250	0.8
DTG-2100	25	60	8	80	10	25	8.0	1.0	200	0.9	25	1.0	250	0.8
DTG-2200	25	80	8	100	10	25	8.0	1.0	200	0.9	25	1.0	250	0.8
DTG-2300	25	100	8	120	10	25	8.0	1.0	200	0.9	25	1.0	250	0.8
DTG-2400	25	120	8	140	10	25	8.0	1.0	200	0.9	25	1.0	250	0.8
DTG-2400M	25	120	10	140	10	25/125	10.0	1.5	500	0.9	25	1.0	250	1.0

Germanium Power Devices Corporation

TO-3

