Ultra High Performance BGA Cooling Solutions w/ Thermal Tape Attachment





ATS Part#: Description:

ATS-52230B-C1-R0

maxiFLOW[™] Heat Sink, T412, BLUE-ANODIZED

Heat Sink Type: maxiFLOW Heat Sink Attachment: Equivalent Part Number: ATS-52230B-C2-R0

THERMAL TAPE

*Image above is for illustration purpose only.

Features & Benefits

- maxiFLOW™ design features a low profile, spread fin array that maximizes surface area for more effective convection (air) cooling
- Fabricated from extruded aluminum, which minimizes thermal resistance from the base to the fins, reduces weight and keeps costs low .
- . Higher performance helps ensure reliable product life at a lower cost than other extruded heat sinks
- Comes pre-assembled with high performance thermal interface material ٠

Thermal Performance

AIR VELOCITY		@200 LFM 1.0 M/S	@300 LFM 1.5 M/S	@400 LFM 2.0 M/S	@500 LFM 2.5 M/S	@600 LFM 3.0 M/S	@700 LFM 3.5 M/S	@800 LFM 4.0 M/S
THERMAL RESISTANCE	Unducted Flow	10.87 °C/W	8.75 °C/W	7.55 °C/W	6.74 °C/W	6.15 °C/W	5.70 °C/W	5.33 °C/W
	Ducted Flow	8.30	n/a	n/a	n/a	n/a	n/a	n/a

Product Detail

Schematic Image	Dimension A	Dimension B	Dimension C	Dimension D	ТІМ	Finish
	23.0 mm	23.0 mm	7.5 mm	37.5 mm	T412	BLUE-ANODIZED
	 Dimensior ATS-5223 (Saint Got Thermal p application ATS reserve performant ATS certification 	ves the right to upda	e provided for referent ate or change its pro	ly with an equivalen nce only. Actual perf ducts without notice -6 and REACH com	t thermal formance to improv	interface material may vary by
*Image above is for illustration purpose only.						

For more information, to find a distributor or to place an order, please contact us at 781-769-2800 (North America), sales@qats.com or www.qats.com.



© 2012 Advanced Thermal Solutions, Inc. | 89-27 Access Road | Norwood MA | 02062 | USA