# Ultra High Performance BGA Cooling Solutions w/ Thermal Tape Attachment





ATS Part#: Description:

#### ATS-52230P-C1-R0

maxiFLOW™ Heat Sink, T412, BLUE-ANODIZED

 Heat Sink Type:
 maxiFLOW

 Heat Sink Attachment:
 THERMAL TAPE

 Equivalent Part Number:
 ATS-52230P-C2-R0

\*Image above is for illustration purpose only.

### **Features & Benefits**

- maxiFLOW™ design features a low profile, spread fin array that maximizes surface area for more effective convection (air) cooling
- · Fabricated from extruded aluminum, which minimizes thermal resistance from the base to the fins, reduces weight and keeps costs low
- · Higher performance helps ensure reliable product life at a lower cost than other extruded heat sinks
- · Comes pre-assembled with high performance thermal interface material

## **Thermal Performance**

AIR VELOCITY		@200 LFM 1.0 M/S	@300 LFM 1.5 M/S	@400 LFM 2.0 M/S	@500 LFM 2.5 M/S	@600 LFM 3.0 M/S	@700 LFM 3.5 M/S	@800 LFM 4.0 M/S
THERMAL RESISTANCE	Unducted Flow	5.06 °C/W	4.17 °C/W	3.64 °C/W	3.28 °C/W	3.02 °C/W	2.81 °C/W	2.65 °C/W
	Ducted Flow	4.13	n/a	n/a	n/a	n/a	n/a	n/a

## **Product Detail**

Schematic Image	Dimension A	Dimension B	Dimension C	Dimension D	ТІМ	Finish
	23.0 mm	23.0 mm	17.5 mm	41.5 mm	T412	BLUE-ANODIZED
	<ul> <li>Dimensior</li> <li>ATS-5223 (Saint Got</li> <li>Thermal p application</li> <li>ATS reserve performant</li> <li>ATS certification</li> </ul>	ves the right to upda	eight from the botton act heat sink assemb provided for referen ate or change its pro- k assembly is RoHS	oly with an equivalen nce only. Actual perf ducts without notice -6 and REACH com	t thermal formance to improv	interface material may vary by
*Image above is for illustration purpose only.						

For more information, to find a distributor or to place an order, please contact us at 781-769-2800 (North America), sales@qats.com or www.qats.com.



© 2012 Advanced Thermal Solutions, Inc. | 89-27 Access Road | Norwood MA | 02062 | USA