

APIX2 Transmitter with Dual Port HDMI and HDCP Support

Data Sheet ADV7682

FEATURES

APIX®2 transmitter with HDCP

High-bandwidth Digital Content Protection (HDCP) 1.4 support with internal preprogrammed HDCP keys

Dual channel encryption engine supports simple daisychain implementation for remote displays

Independent encryption of video and audio

Support for two independent video streams and two synchronous audio streams

Up to 3000 Mbps sustained downstream link bandwidth Up to 187.5 Mbps upstream link bandwidth

Media independent interface (MII), serial port interface (SPI), I²C, and GPIO interfaces for sideband communication

Dual High-Definition Multimedia Interface (HDMI®) receiver Supports all HDMI video resolutions up to the maximum

APIX video link bandwidth of 2.57 Gbps

All mandatory and additional 3D video formats supported

HDCP 1.4 decryption support on each port

 ${\bf Hardware\ controller\ for\ automated\ HDCP\ repeater}$

functions across APIX and HDMI HDCP blocks

HDCP repeater support, up to 24 KSVs supported

Integrated CEC controller, CEC 1.4 compatible

Adaptive TMDS equalizer

ITU-R BT.656 support

8-bit ITU-R BT.656 interface with embedded timing

720p supported at 148.5 MHz clock rate

Audio support

HDMI audio extraction support

Supports multiplexed (TDM) I²S audio I/O

On-chip SRC for synchronization to external master clocks and to synchronize two independent audio streams

General

Dual interrupt controller with APIX link status reporting

Internal EDID RAM

100-lead LQFP_EP, 14 mm × 14 mm package

Qualified for automotive applications

APPLICATIONS

Automotive infotainment

Infotainment head units

Rear seat entertainment systems

Automotive media port applications

HDMI repeaters and video switches

For more information about the ADV7682, including the complete data sheet, contact your local Analog Devices, Inc., sales office at www.analog.com/sales.



Rev. Sp0

Document Feedback

Information furnished by Analog Devices is believed to be accurate and reliable. However, no responsibility is assumed by Analog Devices for its use, nor for any infringements of patents or other rights of third parties that may result from its use. Specifications subject to change without notice. No license is granted by implication or otherwise under any patent or patent rights of Analog Devices. Trademarks and registered trademarks are the property of their respective owners.

SIMPLIFIED FUNCTIONAL BLOCK DIAGRAM




Figure 1.

One Technology Way, P.O. Box 9106, Norwood, MA 02062-9106, U.S.A.
Tel: 781.329.4700 ©2013 Analog Devices, Inc. All rights reserved.
Technical Support www.analog.com

ADV7682 Data Sheet

NOTES

I²C refers to a communications protocol originally developed by Philips Semiconductors (now NXP Semiconductors).

