



# SPC6601

## N & P Pair Enhancement Mode MOSFET

### DESCRIPTION

The SPC6601 is the N- and P-Channel enhancement mode power field effect transistors are produced using high cell density , DMOS trench technology. This high density process is especially tailored to minimize on-state resistance and provide superior switching performance. These devices are particularly suited for low voltage applications such as notebook computer power management and other battery powered circuits where high-side switching , low in-line power loss, and resistance to transients are needed.


### FEATURES

- ◆ N-Channel
  - 30V/2.8A,RDS(ON)= 68mΩ@VGS=10V
  - 30V/2.3A,RDS(ON)= 78mΩ@VGS=4.5V
  - 30V/1.5A,RDS(ON)= 108mΩ@VGS=2.5V
- ◆ P-Channel
  - 30V/-2.8A,RDS(ON)=105mΩ@VGS=- 10V
  - 30V/-2.5A,RDS(ON)=120mΩ@VGS=-4.5V
  - 30V/-1.5A,RDS(ON)=150mΩ@VGS=-2.5V
- ◆ Super high density cell design for extremely low RDS (ON)
- ◆ Exceptional on-resistance and maximum DC current capability
- ◆ TSOT- 23-6P package design


### APPLICATIONS

- Power Management in Note book
- Portable Equipment
- Battery Powered System
- DC/DC Converter
- Load Switch
- DSC
- LCD Display inverter

### PIN CONFIGURATION( TSOT- 23-6P )



### PART MARKING





# SPC6601

## N & P Pair Enhancement Mode MOSFET

### PIN DESCRIPTION

Pin	Symbol	Description
1	G1	Gate 1
2	S2	Source 2
3	G2	Gate 2
4	D2	Drain 2
5	S1	Source 1
6	D1	Drain1

### ORDERING INFORMATION

Part Number	Package	Part Marking
SPC6601TS26RGB	TSOT- 23-6P	01YW

- ※ Week Code : A ~ Z( 1 ~ 26 ) ; a ~ z( 27 ~ 52 )
- ※ SPC6601TS26RGB : Tape Reel ; Pb – Free ; Halogen -Free

### ABSOLUTE MAXIMUM RATINGS

(TA=25°C Unless otherwise noted)

Parameter	Symbol	Typical		Unit
		N-Channel	P-Channel	
Drain-Source Voltage	V <sub>DSS</sub>	30	-30	V
Gate –Source Voltage	V <sub>GSS</sub>	±12	±12	V
Continuous Drain Current(T <sub>J</sub> =150°C)	T <sub>A</sub> =25°C	ID	2.8	A
	T <sub>A</sub> =70°C		2.3	
Pulsed Drain Current	I <sub>DM</sub>	10	-8	A
Continuous Source Current(Diode Conduction)	I <sub>S</sub>	1.25	-1.4	A
Power Dissipation	T <sub>A</sub> =25°C	P <sub>D</sub>	1.15	W
	T <sub>A</sub> =70°C		0.75	
Operating Junction Temperature	T <sub>J</sub>	-55/150		°C
Storage Temperature Range	T <sub>STG</sub>	-55/150		°C
Thermal Resistance-Junction to Ambient	T ≤ 10sec	R <sub>θJA</sub>	50	°C/W
	Steady State		90	



# SPC6601

## N & P Pair Enhancement Mode MOSFET

### ELECTRICAL CHARACTERISTICS

(TA=25°C Unless otherwise noted)





Parameter	Symbol	Conditions	Min.	Typ	Max.	Unit
<b>Static</b>						
Drain-Source Breakdown Voltage	V <sub>(BR)DSS</sub>	V <sub>GS</sub> =0V, I <sub>D</sub> = 250uA	N-Ch	30		V
		V <sub>GS</sub> =0V, I <sub>D</sub> =-250uA	P-Ch	-30		
Gate Threshold Voltage	V <sub>GS(th)</sub>	V <sub>DS</sub> =V <sub>GS</sub> , I <sub>D</sub> =250uA	N-Ch	0.8		1.6
		V <sub>DS</sub> =V <sub>GS</sub> , I <sub>D</sub> =-250uA	P-Ch	-0.4		-1.0
Gate Leakage Current	I <sub>GSS</sub>	V <sub>DS</sub> =0V, V <sub>GS</sub> =±12V	N-Ch		±100	nA
		V <sub>DS</sub> =0V, V <sub>GS</sub> =±12V	P-Ch		±100	
Zero Gate Voltage Drain Current	I <sub>DSS</sub>	V <sub>DS</sub> = 21V, V <sub>GS</sub> =0V	N-Ch		1	uA
		V <sub>DS</sub> =-21V, V <sub>GS</sub> =0V	P-Ch		-1	
		V <sub>DS</sub> = 21V, V <sub>GS</sub> =0V T <sub>J</sub> =55°C	N-Ch		10	
		V <sub>DS</sub> =-21V, V <sub>GS</sub> =0V T <sub>J</sub> =55°C	P-Ch		-10	
On-State Drain Current	I <sub>D(on)</sub>	V <sub>DS</sub> ≥ 5V, V <sub>GS</sub> = 10V	N-Ch	6		A
		V <sub>DS</sub> ≤ -5V, V <sub>GS</sub> =-10V	P-Ch	-6		
Drain-Source On-Resistance	R <sub>D(on)</sub>	V <sub>GS</sub> = 10V, I <sub>D</sub> = 2.8A	N-Ch		0.048	0.068
		V <sub>GS</sub> =-10V, I <sub>D</sub> =-2.8A	P-Ch		0.077	0.105
		V <sub>GS</sub> = 4.5V, I <sub>D</sub> = 2.3A	N-Ch		0.054	0.078
		V <sub>GS</sub> =-4.5V, I <sub>D</sub> =-2.5A	P-Ch		0.092	0.120
		V <sub>GS</sub> = 2.5V, I <sub>D</sub> = 1.5A	N-Ch		0.079	0.108
		V <sub>GS</sub> =-2.5V, I <sub>D</sub> =-1.5A	P-Ch		0.118	0.150
Forward Transconductance	g <sub>fs</sub>	V <sub>DS</sub> =4.5V, I <sub>D</sub> =2.8A	N-Ch		4.6	S
		V <sub>DS</sub> =-10V, I <sub>D</sub> =-2.8A	P-Ch		4	
Diode Forward Voltage	V <sub>SD</sub>	I <sub>S</sub> = 1.25A, V <sub>GS</sub> =0V	N-Ch		0.8	1.2
		I <sub>S</sub> =-1.2A, V <sub>GS</sub> =0V	P-Ch		-0.8	-1.2
<b>Dynamic</b>						
Total Gate Charge	Q <sub>g</sub>	N-Channel V <sub>DS</sub> =15 , V <sub>GS</sub> =4.5V , I <sub>D</sub> =2.0A P-Channel V <sub>DS</sub> =-15V , V <sub>GS</sub> =-4.5V , I <sub>D</sub> =-2.0A	N-Ch		4.2	6
Gate-Source Charge	Q <sub>gs</sub>		P-Ch		5.8	
Gate-Drain Charge	Q <sub>gd</sub>		N-Ch		0.6	
Turn-On Time	t <sub>d(on)</sub>		P-Ch		0.8	
	t <sub>r</sub>		N-Ch		1.5	
Turn-Off Time	t <sub>d(off)</sub>	N-Channel V <sub>DD</sub> =15 , R <sub>L</sub> =10Ω V <sub>GEN</sub> =10V , R <sub>G</sub> =3Ω  P-Channel V <sub>DD</sub> =-15V , R <sub>L</sub> =15Ω V <sub>GEN</sub> =-10V , R <sub>G</sub> =3Ω	P-Ch		2.5	nS
	t <sub>f</sub>		N-Ch		6	
			P-Ch		2.5	
			N-Ch		3.9	
			P-Ch		20	
			N-Ch		40	
			P-Ch		4	
			N-Ch		15	



# SPC6601

## N & P Pair Enhancement Mode MOSFET

### TYPICAL CHARACTERISTICS ( N-Channel )









# SPC6601

## N & P Pair Enhancement Mode MOSFET

### TYPICAL CHARACTERISTICS ( N-Channel )








# SPC6601

## N & P Pair Enhancement Mode MOSFET

### TYPICAL CHARACTERISTICS ( N-Channel )









# SPC6601

## N & P Pair Enhancement Mode MOSFET

### TYPICAL CHARACTERISTICS ( P-Channel )









# SPC6601

## N & P Pair Enhancement Mode MOSFET

### TYPICAL CHARACTERISTICS ( P-Channel )








# SPC6601

## N & P Pair Enhancement Mode MOSFET

### TYPICAL CHARACTERISTICS (P-Channel)






# SPC6601

## N & P Pair Enhancement Mode MOSFET

### TSOT-23- 6P PACKAGE OUTLINE



SYMBOL	VARIATION					
	Millimeters			Inches		
	Min	Nom	Max	Min	Nom	Max
A	0.700	0.860	1.000	0.028	0.034	0.040
A1	0.000	0.060	0.100	0.000	0.002	0.004
A2	0.700	0.800	0.900	0.028	0.031	0.035
A3	—	0.420	0.520	—	0.017	0.020
b	0.300	0.425	0.500	0.012	0.017	0.020
c	0.080	0.138	0.200	0.003	0.005	0.008
D	2.692	2.900	3.099	0.106	0.114	0.122
E	2.591	2.800	3.000	0.102	0.110	0.118
E1	1.397	1.600	1.803	0.055	0.063	0.071
e	0.950 BSC			0.037 BSC		
e1	1.900 BSC			0.075 BSC		
L	0.300	0.450	0.600	0.012	0.018	0.024
L1	0.600 REF			0.024 REF		
L2	0.250 BSC			0.010 BSC		
R	0.100	—	—	0.004	—	—
R1	0.100	—	0.250	0.004	—	0.010
$\theta$	0°	—	6°	0°	—	6°



# SPC6601

## N & P Pair Enhancement Mode MOSFET

---

Information provided is alleged to be exact and consistent. SYNC Power Corporation presumes no responsibility for the penalties of use of such information or for any violation of patents or other rights of third parties which may result from its use. No license is granted by allegation or otherwise under any patent or patent rights of SYNC Power Corporation. Conditions mentioned in this publication are subject to change without notice. This publication surpasses and replaces all information previously supplied. SYNC Power Corporation products are not authorized for use as critical components in life support devices or systems without express written approval of SYNC Power Corporation.

©The SYNC Power logo is a registered trademark of SYNC Power Corporation

©2004 SYNC Power Corporation – Printed in Taiwan – All Rights Reserved

SYNC Power Corporation

7F-2, No.3-1, Park Street

NanKang District (NKSP), Taipei, Taiwan 115

Phone: 886-2-2655-8178

Fax: 886-2-2655-8468

©<http://www.syncpower.com>