


1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
VSS	VDD	RS	R/W	E	D7	D6	D5	D4	D3	D2	D1	D0	CS1	CS2	CS3	CS4	RES	K	A

NOTES:

1. DISPLAY TYPE: STN or FSTN
2. VIEWING DIRECTION: 6:00 or 12:00
3. POLARIZER MODE: TRANFLECTIVE or TRANSMISSIVE
4. DRIVE METHOD: 1/64 DUTY 1/9 BIAS
5. LCD OPERATING VOLTAGE: 11.0V
6. OPERATING TEMP: NORMAL or WIDE
7. STORAGE TEMP: NORMAL or WIDE
8. CONTROLLER: S6B0108A01-COCX
9. BACKLIGHT: LED or NONE
10. BEZEL IS TO BE PAINTED BLACK
11. UNMARKED TOLERANCE: ±0.3mm

DETAIL A:



TIAN-MA MICROELECTRONICS CO.

6/F., CASTIC Building, Shennan Road, Central, Shenzhen, China

DRAWN BY:	TITLE: TM24064Q series	
CHECKED BY:	DWG NO: G-1	
APPROVED BY:	DWG NAME: TM24064QBCWU66-1	UNIT: mm
CONFIRMED BY:	SHEET NO: 1 OF 1	