



Search

[Home](#)
[Products](#)
[Support](#)
[Services](#)
[Selectors](#)
[How to Buy](#)

Rack PDU, Basic, 1U, 30A, 208V, (12) C13

APC Basic Rack PDU , Input: 208V , Input Connections: NEMA L6-30P , Cord Length: 12 feet (3.66 meters) , Output: 208V , Output Connections: IEC 320 C13

Includes: Installation Guide, Rack Mounting Brackets, User Manual

Part Number : **AP9571**



- [Compare Models](#)
- [Email Technical Specifications](#)
- [Printer Friendly](#)


Additional Information

- [Product Overview](#)
- [User Manual & Installation Guides](#)
- [Product Distribution](#)


[\[+\] More Images](#)

Technical Specifications

Output

| | | |
|--------------------------------------|------------------|---|
| Nominal Output Voltage | 208V | |
| Maximum Total Current Draw per Phase | 24A | |
| Output Connections | (12) IEC 320 C13 |  |
| Always on Outlets | 12 | |
| Overload Protection | Yes | |


Options:

- o [AC Connections](#)

Features:

- o Rack-Mountable
- o Single-branch power input

Input

| | | |
|----------------------------------|------------------------|---|
| Nominal Input Voltage | 208V | |
| Input Frequency | 50/60 Hz | |
| Regulatory Derated Input Current | 24A | |
| Input Connections | NEMA L6-30P |  |
| Cord Length | 12 feet (3.66 meters) | |
| Acceptable Input Voltage | 200-240 VAC | |
| Maximum Line Current per phase | 30A | |
| Maximum Input Current per phase | 30A | |
| Load Capacity | 4992 VA | |

Physical

| | |
|-----------------|-----------------------|
| Net Weight | 5.60 lbs. (2.55 kg) |
| Maximum Height | 1.70 inches (43 mm) |
| Maximum Width | 17.50 inches (445 mm) |
| Maximum depth | 2.50 inches (64 mm) |
| Shipping Weight | 8.00 lbs. (3.64 kg) |
| Shipping Height | 6.00 inches (152 mm) |
| Shipping Width | 19.12 inches (486 mm) |
| Shipping Depth | 6.95 inches (177 mm) |
| Color | Black |

Environmental

| | |
|-----------------------------|-------------------------------|
| Operating Environment | -15 - 45 °C (5 - 113 °F) |
| Operating Relative Humidity | 5 - 95% |
| Operating Elevation | 0-15000 feet (0-4500 meters) |
| Storage Temperature | -25 - 65 °C (-13 - 149 °F) |
| Storage Relative Humidity | 5 - 95% |
| Storage Elevation | 0-50000 feet (0-15000 meters) |

Conformance

| | |
|----------------------|-------------------------------|
| Regulatory Approvals | cUL Listed,UL 60950,UL Listed |
| Standard Warranty | 2 years repair or replace |

[Copyright](#) © American Power Conversion Corp., all rights reserved

[About APC](#)[Investors](#)[Job Seekers](#)[Press](#)[Feedback](#)[Contact](#)[Privacy](#) [Policy](#)