

IRLR9343PbF


IRLU9343PbF

IRLU9343-701PbF

Features

- Advanced Process Technology
- Key Parameters Optimized for Class-D Audio Amplifier Applications
- Low $R_{DS(on)}$ for Improved Efficiency
- Low Q_g and Q_{sw} for Better THD and Improved Efficiency
- Low Q_{rr} for Better THD and Lower EMI
- 175°C Operating Junction Temperature for Ruggedness
- Repetitive Avalanche Capability for Robustness and Reliability
- Multiple Package Options
- Lead-Free

| Key Parameters | | |
|--------------------------------------|-----|------------------|
| V_{DS} | -55 | V |
| $R_{DS(on)}$ typ. @ $V_{GS} = -10V$ | 93 | $\text{m}\Omega$ |
| $R_{DS(on)}$ typ. @ $V_{GS} = -4.5V$ | 150 | $\text{m}\Omega$ |
| Q_g typ. | 31 | nC |
| T_J max | 175 | °C |



Description

This Digital Audio HEXFET® is specifically designed for Class-D audio amplifier applications. This MosFET utilizes the latest processing techniques to achieve low on-resistance per silicon area. Furthermore, Gate charge, body-diode reverse recovery and internal Gate resistance are optimized to improve key Class-D audio amplifier performance factors such as efficiency, THD and EMI. Additional features of this MosFET are 175°C operating junction temperature and repetitive avalanche capability. These features combine to make this MosFET a highly efficient, robust and reliable device for Class-D audio amplifier applications.

Absolute Maximum Ratings

| | Parameter | Max. | Units |
|-----------------------------------|--|--------------|-------|
| V_{DS} | Drain-to-Source Voltage | -55 | V |
| V_{GS} | Gate-to-Source Voltage | ± 20 | |
| I_D @ $T_C = 25^\circ\text{C}$ | Continuous Drain Current, $V_{GS} @ -10V$ | -20 | A |
| I_D @ $T_C = 100^\circ\text{C}$ | Continuous Drain Current, $V_{GS} @ 10V$ | -14 | |
| I_{DM} | Pulsed Drain Current ① | -60 | |
| P_D @ $T_C = 25^\circ\text{C}$ | Power Dissipation | 79 | W |
| P_D @ $T_C = 100^\circ\text{C}$ | Power Dissipation | 39 | |
| | Linear Derating Factor | 0.53 | W/°C |
| T_J | Operating Junction and Storage Temperature Range | -40 to + 175 | °C |
| T_{STG} | | | |
| | Clamping Pressure ⑥ | — | N |

Thermal Resistance

| | Parameter | Typ. | Max. | Units |
|-----------|--------------------------------------|------|------|-------|
| $R_{θJC}$ | Junction-to-Case ⑤ | — | 1.9 | |
| $R_{θJA}$ | Junction-to-Ambient (PCB Mounted) ⑤⑧ | — | 50 | °C/W |
| $R_{θJA}$ | Junction-to-Ambient (free air) ⑤ | — | 110 | |

Notes ① through ⑨ are on page 10

12/07/04

Electrical Characteristics @ $T_J = 25^\circ\text{C}$ (unless otherwise specified)

| | Parameter | Min. | Typ. | Max. | Units | Conditions |
|--|--------------------------------------|------|------|------|----------------------|---|
| BV_{DSS} | Drain-to-Source Breakdown Voltage | -55 | — | — | V | $V_{\text{GS}} = 0\text{V}$, $I_D = -250\mu\text{A}$ |
| $\Delta \text{BV}_{\text{DSS}}/\Delta T_J$ | Breakdown Voltage Temp. Coefficient | — | -52 | — | mV/ $^\circ\text{C}$ | Reference to 25°C , $I_D = -1\text{mA}$ |
| $R_{\text{DS(on)}}$ | Static Drain-to-Source On-Resistance | — | 93 | 105 | $\text{m}\Omega$ | $V_{\text{GS}} = -10\text{V}$, $I_D = -3.4\text{A}$ ③ |
| | | — | 150 | 170 | | $V_{\text{GS}} = -4.5\text{V}$, $I_D = -2.7\text{A}$ ③ |
| $V_{\text{GS(th)}}$ | Gate Threshold Voltage | -1.0 | — | — | V | $V_{\text{DS}} = V_{\text{GS}}$, $I_D = -250\mu\text{A}$ |
| $\Delta V_{\text{GS(th)}}/\Delta T_J$ | Gate Threshold Voltage Coefficient | — | -3.7 | — | mV/ $^\circ\text{C}$ | |
| I_{DSS} | Drain-to-Source Leakage Current | — | — | -2.0 | μA | $V_{\text{DS}} = -55\text{V}$, $V_{\text{GS}} = 0\text{V}$ |
| | | — | — | -25 | | $V_{\text{DS}} = -55\text{V}$, $V_{\text{GS}} = 0\text{V}$, $T_J = 125^\circ\text{C}$ |
| I_{GSS} | Gate-to-Source Forward Leakage | — | — | -100 | nA | $V_{\text{GS}} = -20\text{V}$ |
| | Gate-to-Source Reverse Leakage | — | — | 100 | | $V_{\text{GS}} = 20\text{V}$ |
| g_{fs} | Forward Transconductance | 5.3 | — | — | S | $V_{\text{DS}} = -25\text{V}$, $I_D = -14\text{A}$ |
| Q_g | Total Gate Charge | — | 31 | 47 | | $V_{\text{DS}} = -44\text{V}$ |
| Q_{gs} | Gate-to-Source Charge | — | 7.1 | — | | $V_{\text{GS}} = -10\text{V}$ |
| Q_{gd} | Gate-to-Drain Charge | — | 8.5 | — | | $I_D = -14\text{A}$ |
| Q_{godr} | Gate Charge Overdrive | — | 15 | — | | See Fig. 6 and 19 |
| $t_{\text{d(on)}}$ | Turn-On Delay Time | — | 9.5 | — | ns | $V_{\text{DD}} = -28\text{V}$, $V_{\text{GS}} = -10\text{V}$ ③ |
| t_r | Rise Time | — | 24 | — | | $I_D = -14\text{A}$ |
| $t_{\text{d(off)}}$ | Turn-Off Delay Time | — | 21 | — | | $R_G = 2.5\Omega$ |
| t_f | Fall Time | — | 9.5 | — | | |
| C_{iss} | Input Capacitance | — | 660 | — | pF | $V_{\text{GS}} = 0\text{V}$ |
| C_{oss} | Output Capacitance | — | 160 | — | | $V_{\text{DS}} = -50\text{V}$ |
| C_{rss} | Reverse Transfer Capacitance | — | 72 | — | | $f = 1.0\text{MHz}$, See Fig.5 |
| C_{osss} | Effective Output Capacitance | — | 280 | — | | $V_{\text{GS}} = 0\text{V}$, $V_{\text{DS}} = 0\text{V}$ to -44V |
| L_D | Internal Drain Inductance | — | 4.5 | — | nH | Between lead, 6mm (0.25in.) from package |
| L_S | Internal Source Inductance | — | 7.5 | — | | and center of die contact ④ |

Avalanche Characteristics

| | Parameter | Typ. | Max. | Units |
|-----------------|---------------------------------|---------------------------|------|-------------|
| E_{AS} | Single Pulse Avalanche Energy ② | — | 120 | mJ |
| I_{AR} | Avalanche Current ⑦ | See Fig. 14, 15, 17a, 17b | A | mJ |
| E_{AR} | Repetitive Avalanche Energy ⑦ | | | |

Diode Characteristics

| | Parameter | Min. | Typ. | Max. | Units | Conditions |
|--------------------------------|---|------|------|------|-------|--|
| $I_S @ T_C = 25^\circ\text{C}$ | Continuous Source Current (Body Diode) | — | — | -20 | A | MOSFET symbol showing the integral reverse p-n junction diode. |
| | Pulsed Source Current (Body Diode) ① | — | — | -60 | | |
| V_{SD} | Diode Forward Voltage | — | — | -1.2 | V | $T_J = 25^\circ\text{C}$, $I_S = -14\text{A}$, $V_{\text{GS}} = 0\text{V}$ ③ |
| t_{rr} | Reverse Recovery Time | — | 57 | 86 | ns | $T_J = 25^\circ\text{C}$, $I_F = -14\text{A}$ |
| Q_{rr} | Reverse Recovery Charge | — | 120 | 180 | nC | $dI/dt = 100\text{A}/\mu\text{s}$ ③ |




Fig 1. Typical Output Characteristics




Fig 2. Typical Output Characteristics




Fig 3. Typical Transfer Characteristics




Fig 4. Normalized On-Resistance vs. Temperature




Fig 5. Typical Capacitance vs. Drain-to-Source Voltage

Document Number: 91341




Fig 6. Typical Gate Charge vs. Gate-to-Source Voltage

www.vishay.com

IRLR/U9343PbF & IRLU9343-701PbF

International
Rectifier




Fig 7. Typical Source-Drain Diode Forward Voltage




Fig 8. Maximum Safe Operating Area




Fig 9. Maximum Drain Current vs. Case Temperature




Fig 10. Threshold Voltage vs. Temperature




Fig 11. Maximum Effective Transient Thermal Impedance, Junction-to-Case




Fig 12. On-Resistance Vs. Gate Voltage




Fig 13. Maximum Avalanche Energy Vs. Drain Current




Fig 14. Typical Avalanche Current Vs. Pulsewidth




Fig 15. Maximum Avalanche Energy Vs. Temperature

Notes on Repetitive Avalanche Curves , Figures 14, 15:
(For further info, see AN-1005 at www.irf.com)

1. Avalanche failures assumption:
Purely a thermal phenomenon and failure occurs at a temperature far in excess of T_{jmax} . This is validated for every part type.
2. Safe operation in Avalanche is allowed as long as T_{jmax} is not exceeded.
3. Equation below based on circuit and waveforms shown in Figures 17a, 17b.
4. $P_D(\text{ave})$ = Average power dissipation per single avalanche pulse.
5. BV = Rated breakdown voltage (1.3 factor accounts for voltage increase during avalanche).
6. I_{av} = Allowable avalanche current.
7. ΔT = Allowable rise in junction temperature, not to exceed T_{jmax} (assumed as $25^\circ C$ in Figure 14, 15).

t_{av} = Average time in avalanche.

D = Duty cycle in avalanche = $t_{av} \cdot f$

$Z_{thJC}(D, t_{av})$ = Transient thermal resistance, see figure 11)

$$P_D(\text{ave}) = 1/2 (1.3 \cdot BV \cdot I_{av}) = \Delta T / Z_{thJC}$$

$$I_{av} = 2\Delta T / [1.3 \cdot BV \cdot Z_{th}]$$

$$E_{AS}(\text{AR}) = P_D(\text{ave}) \cdot t_{av}$$

IRLR/U9343PbF & IRLU9343-701PbF

International
Rectifier





Fig 16. Peak Diode Recovery dv/dt Test Circuit for P-Channel HEXFET® Power MOSFETs




Fig 17a. Unclamped Inductive Test Circuit




Fig 18a. Switching Time Test Circuit




Fig 17b. Unclamped Inductive Waveforms




Fig 18b. Switching Time Waveforms




Fig 19a. Gate Charge Test Circuit





Fig 19b Gate Charge Waveform

D-Pak (TO-252AA) Package Outline

Dimensions are shown in millimeters (inches)



NOTES:

- 1.0 DIMENSIONING AND TOLERANCING PER ASME Y14.5 M- 1994.
- 2.0 DIMENSIONS ARE SHOWN IN INCHES [MILLIMETERS].
- 3.0 LEAD DIMENSION UNCONTROLLED IN L5
- 4.0 DIMENSION D1 AND E1 ESTABLISH A MINIMUM MOUNTING SURFACE FOR THERMAL PAD.
- 5.0 SECTION C-C DIMENSIONS APPLY TO THE FLAT SECTION OF THE LEAD BETWEEN .005 [0.127] AND .010 [0.254] FROM THE LEAD TIP.
- 6.0 DIMENSION D & E DO NOT INCLUDE MOLD FLASH. MOLD FLASH SHALL NOT EXCEED .005" (0.127) PER SIDE. THESE DIMENSIONS ARE MEASURED AT THE OUTERMOST EXTREMES OF THE PLASTIC BODY.
- 7.0 OUTLINE CONFORMS TO JEDEC OUTLINE TO-252AA.

| SYMBOL | DIMENSIONS | | | | NOTES | |
|--------|-------------|-------|-----------|------|-------|--|
| | MILLIMETERS | | INCHES | | | |
| | MIN. | MAX. | MIN. | MAX. | | |
| A | 2.18 | 2.39 | .086 | .094 | | |
| A1 | | 0.13 | | .005 | | |
| b | 0.64 | 0.89 | .025 | .035 | 5 | |
| b1 | 0.64 | 0.79 | .025 | .031 | 5 | |
| b2 | 0.76 | 1.14 | .030 | .045 | | |
| b3 | 4.95 | 5.46 | .195 | .215 | | |
| c | 0.46 | 0.61 | .018 | .024 | 5 | |
| c1 | 0.41 | 0.56 | .016 | .022 | 5 | |
| c2 | .046 | 0.89 | .018 | .035 | 5 | |
| D | 5.97 | 6.22 | .235 | .245 | 6 | |
| D1 | 5.21 | - | .205 | - | 4 | |
| E | 6.35 | 6.73 | .250 | .265 | 6 | |
| E1 | 4.32 | - | .170 | - | 4 | |
| e | 2.29 | | .090 BSC | | | |
| H | 9.40 | 10.41 | .370 | .410 | | |
| L | 1.40 | 1.78 | .055 | .070 | | |
| L1 | 2.74 REF. | | .108 REF. | | | |
| L2 | 0.051 BSC | | .020 BSC | | | |
| L3 | 0.89 | 1.27 | .035 | .050 | | |
| L4 | | 1.02 | | .040 | | |
| L5 | 1.14 | 1.52 | .045 | .060 | 3 | |
| Ø | 0° | 10° | 0° | 10° | | |
| Ø1 | 0° | 15° | 0° | 15° | | |

LEAD ASSIGNMENTS

HEXFET

- 1.- GATE
- 2.- DRAIN
- 3.- SOURCE
- 4.- DRAIN


IGBTs, CoPACK

- 1.- GATE
- 2.- COLLECTOR
- 3.- Emitter
- 4.- COLLECTOR


D-Pak (TO-252AA) Part Marking Information

EXAMPLE: THIS IS AN IRFR120
WITH ASSEMBLY
LOT CODE 1234
ASSEMBLED ON WV 16, 1999
IN THE ASSEMBLY LINE "A"

Note: "P" in assembly line position
indicates "Lead-Free"




OR



I-Pak (TO-251AA) Package Outline

Dimensions are shown in millimeters (inches)



NOTES:

- 1 DIMENSIONING AND TOLERANCING PER ASME Y14.5 M- 1994.
- 2 DIMENSIONS ARE SHOWN IN MILLIMETERS [INCHES].
- 3 DIMENSION D & E DO NOT INCLUDE MOLD FLASH. MOLD FLASH SHALL NOT EXCEED 0.005" (0.127) PER SIDE. THESE DIMENSIONS ARE MEASURED AT THE OUTERMOST EXTREMES OF THE PLASTIC BODY.
- 4 THERMAL PAD CONTOUR OPTION WITHIN DIMENSION b4, L2, E1 & D1.
- 5 LEAD DIMENSION UNCONTROLLED IN L3.
- 6 DIMENSION b1, b3 APPLY TO BASE METAL ONLY.
- 7 OUTLINE CONFORMS TO JEDEC OUTLINE TO-251AA.
- 8 CONTROLLING DIMENSION : INCHES.

LEAD ASSIGNMENTS

| SYMBOL | DIMENSIONS | | | | NOTES | |
|--------|-------------|------|-----------|-------|-------|--|
| | MILLIMETERS | | INCHES | | | |
| | MIN. | MAX. | MIN. | MAX. | | |
| A | 2.18 | 2.39 | 0.086 | .094 | | |
| A1 | 0.89 | 1.14 | 0.035 | 0.045 | | |
| b | 0.64 | 0.89 | 0.025 | 0.035 | | |
| b1 | 0.64 | 0.79 | 0.025 | 0.031 | 4 | |
| b2 | 0.76 | 1.14 | 0.030 | 0.045 | | |
| b3 | 0.76 | 1.04 | 0.030 | 0.041 | | |
| b4 | 5.00 | 5.46 | 0.195 | 0.215 | 4 | |
| c | 0.46 | 0.61 | 0.018 | 0.024 | | |
| c1 | 0.41 | 0.56 | 0.016 | 0.022 | | |
| c2 | .046 | 0.86 | 0.018 | 0.035 | | |
| D | 5.97 | 6.22 | 0.235 | 0.245 | 3, 4 | |
| D1 | 5.21 | - | 0.205 | - | 4 | |
| E | 6.35 | 6.73 | 0.250 | 0.265 | 3, 4 | |
| E1 | 4.32 | - | 0.170 | - | 4 | |
| e | 2.29 | | 0.090 BSC | | | |
| L | 8.89 | 9.60 | 0.350 | 0.380 | | |
| L1 | 1.91 | 2.29 | 0.075 | 0.090 | | |
| L2 | 0.89 | 1.27 | 0.035 | 0.050 | 4 | |
| L3 | 1.14 | 1.52 | 0.045 | 0.060 | 5 | |
| Ø1 | 0" | 15" | 0" | 15" | | |


HEXFET

- 1.- GATE
- 2.- DRAIN
- 3.- SOURCE
- 4.- DRAIN


I-Pak (TO-251AA) Part Marking Information

EXAMPLE: THIS IS AN IRFU120
WITH ASSEMBLY
LOT CODE 5678
ASSEMBLED ON WW 19, 1999
IN THE ASSEMBLY LINE "A"

Note: "P" in assembly line
position indicates "Lead-Free"




OR




D-Pak (TO-252AA) Tape & Reel Information

Dimensions are shown in millimeters (inches)



NOTES :

1. CONTROLLING DIMENSION : MILLIMETER.
2. ALL DIMENSIONS ARE SHOWN IN MILLIMETERS (INCHES).
3. OUTLINE CONFORMS TO EIA-481 & EIA-541.



NOTES :


1. OUTLINE CONFORMS TO EIA-481.

IRLR/U9343PbF & IRLU9343-701PbF

International
IR Rectifier

I-Pak Leadform Option 701 Package Outline ⑨

Dimensions are shown in millimeters (inches)



- 1-. GATE
- 2-. DRAIN
- 3-. SOURCE
- 4-. DRAIN

NOTES:

- 1.0 CONTROL DIMENSIONS IN INCHES
- 2.0 PARALLELISM AND ANGULARITY MAX. 0.076 (0.003)
- 3.0 LEADFORM CRITICAL DIMENSIONS DOUBLE RINGED

Notes:

- ① Repetitive rating; pulse width limited by max. junction temperature.
- ② Starting $T_J = 25^\circ\text{C}$, $L = 1.24\text{mH}$, $R_G = 25\Omega$, $I_{AS} = -14\text{A}$.
- ③ Pulse width $\leq 400\mu\text{s}$; duty cycle $\leq 2\%$.
- ④ This only applies for I-Pak, L_S of D-Pak is measured between lead and center of die contact
- ⑤ R_θ is measured at T_J of approximately 90°C .
- ⑥ Contact factory for mounting information
- ⑦ Limited by T_{Jmax} . See Figs. 14, 15, 17a, 17b for repetitive avalanche information
- ⑧ When D-Pak mounted on 1" square PCB (FR-4 or G-10 Material). For recommended footprint and soldering techniques refer to application note #AN-994
- ⑨ Refer to D-Pak package for Part Marking, Tape and Reel information.

Data and specifications subject to change without notice.
This product has been designed for the Industrial market.
Qualification Standards can be found on IR's Web site.

International
IR Rectifier

IR WORLD HEADQUARTERS: 233 Kansas St., El Segundo, California 90245, USA Tel: (310) 252-7105
TAC Fax: (310) 252-7903
12/04



Legal Disclaimer Notice

Vishay

Notice

Specifications of the products displayed herein are subject to change without notice. Vishay Intertechnology, Inc., or anyone on its behalf, assumes no responsibility or liability for any errors or inaccuracies.

Information contained herein is intended to provide a product description only. No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document. Except as provided in Vishay's terms and conditions of sale for such products, Vishay assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of Vishay products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Vishay for any damages resulting from such improper use or sale.