

Single Supply, High Slew Rate Low Input Offset Voltage, Bipolar Operational Amplifiers

The MC33272/74 series of monolithic operational amplifiers are quality fabricated with innovative Bipolar design concepts. This dual and quad operational amplifier series incorporates Bipolar inputs along with a patented Zip-R-Trim element for input offset voltage reduction. The MC33272/74 series of operational amplifiers exhibits low input offset voltage and high gain bandwidth product. Dual-doublet frequency compensation is used to increase the slew rate while maintaining low input noise characteristics. Its all NPN output stage exhibits no deadband crossover distortion, large output voltage swing, and an excellent phase and gain margin. It also provides a low open-loop high frequency output impedance with symmetrical source and sink AC frequency performance.

The MC33272/74 series is specified over -40°C to $+85^{\circ}\text{C}$ and is available in the plastic DIP and SOIC surface mount packages (P and D suffixes).

- Input Offset Voltage Trimmed to 100 μV (Typ)
- Low Input Bias Current: 300 nA
- Low Input Offset Current: 3.0 nA
- High Input Resistance: 16 M Ω
- Low Noise: 18 nV/ $\sqrt{\text{Hz}}$ @ 1.0 kHz
- High Gain Bandwidth Product: 24 MHz @ 100 kHz
- High Slew Rate: 10 V/ μs
- Power Bandwidth: 160 kHz
- Excellent Frequency Stability
- Unity Gain Stable: w/Capacitance Loads to 500 pF
- Large Output Voltage Swing: +14.1 V / -14.6 V
- Low Total Harmonic Distortion: 0.003%
- Power Supply Drain Current: 2.15 mA per Amplifier
- Single or Split Supply Operation: +3.0 V to +36 V or ± 1.5 V to ± 18 V
- ESD Diodes Provide Added Protection to the Inputs

ORDERING INFORMATION

Op Amp Function	Device	Specified Ambient Temperature Range	Package
Dual	MC33272D	-40°C to $+85^{\circ}\text{C}$	SO-8
	MC33272P		Plastic DIP
Quad	MC33274D	-40°C to $+85^{\circ}\text{C}$	SO-14
	MC33274P		Plastic DIP

HIGH PERFORMANCE OPERATIONAL AMPLIFIERS

SILICON MONOLITHIC INTEGRATED CIRCUIT

DUAL




P SUFFIX
PLASTIC PACKAGE
CASE 626



D SUFFIX
PLASTIC PACKAGE
CASE 751
(SO-8)

PIN CONNECTIONS



QUAD




P SUFFIX
PLASTIC PACKAGE
CASE 646



D SUFFIX
PLASTIC PACKAGE
CASE 751A
(SO-14)

PIN CONNECTIONS



MC33272, MC33274

MAXIMUM RATINGS

2

Rating	Symbol	Value	Unit
Supply Voltage	V _{CC} to V _{EE}	+36	V
Input Differential Voltage Range	V _{IDR}	(Note 1)	V
Input Voltage Range	V _{IR}	(Note 1)	V
Output Short Circuit Duration (Note 2)	t _{SC}	Indefinite	sec
Maximum Junction Temperature	T _J	+150	°C
Storage Temperature	T _{stg}	-60 to +150	°C
Maximum Power Dissipation	P _D	(Note 2)	mW

- NOTES:**
1. Either or both input voltages should not exceed V_{CC} or V_{EE}.
 2. Power dissipation must be considered to ensure maximum junction temperature (T_J) is not exceeded (see Figure 2).

DC ELECTRICAL CHARACTERISTICS (V_{CC} = +15 V, V_{EE} = -15 V, T_A = 25°C, unless otherwise noted.)

Characteristics	Figure	Symbol	Min	Typ	Max	Unit
Input Offset Voltage (R _S = 10 Ω, V _{CM} = 0 V, V _O = 0 V) (V _{CC} = +15 V, V _{EE} = -15 V) T _A = +25°C T _A = -40° to +85°C (V _{CC} = 5.0 V, V _{EE} = 0 V) T _A = +25°C	3	V _{IO}	—	0.1	1.0	mV
Average Temperature Coefficient of Input Offset Voltage R _S = 10 Ω, V _{CM} = 0 V, V _O = 0 V, T _A = -40° to +85°C	3	ΔV _{IO} /ΔT	—	2.0	—	μV/°C
Input Bias Current (V _{CM} = 0 V, V _O = 0 V) T _A = +25°C T _A = -40° to +85°C	4, 5	I _{IB}	—	300	650 800	nA
Input Offset Current (V _{CM} = 0 V, V _O = 0 V) T _A = +25°C T _A = -40° to +85°C		I _{IO}	—	3.0	65 80	nA
Common Mode Input Voltage Range (ΔV _{IO} = 5.0 mV, V _O = 0 V) T _A = +25°C	6	V _{ICR}	V _{EE} to (V _{CC} - 1.8)			V
Large Signal Voltage Gain (V _O = 0 V to 10 V, R _L = 2.0 kΩ) T _A = +25°C T _A = -40° to +85°C	7	AVOL	90 86	100	—	dB
Output Voltage Swing (V _{ID} = ±1.0 V) (V _{CC} = +15 V, V _{EE} = -15 V) R _L = 2.0 kΩ R _L = 2.0 kΩ R _L = 10 kΩ R _L = 10 kΩ (V _{CC} = 5.0 V, V _{EE} = 0 V) R _L = 2.0 kΩ R _L = 2.0 kΩ	8, 9, 12 10, 11	V _{O+} V _{O-} V _{O+} V _{O-} V _{OL} V _{OH}	13.4 — 13.4 — — 3.7	13.9 -13.9 14 — — —	-13.5 — — -14.7 0.2 5.0	V
Common Mode Rejection (V _{in} = +13.2 V to -15 V)	13	CMR	80	100	—	dB
Power Supply Rejection V _{CC} /V _{EE} = +15 V/-15 V, +5.0 V/-15 V, +15 V/-5.0 V	14, 15	PSR	80	105	—	dB
Output Short Circuit Current (V _{ID} = 1.0 V, Output to Ground) Source Sink	16	I _{SC}	+25 -25	+37 -37	—	mA
Power Supply Current Per Amplifier (V _O = 0 V) (V _{CC} = +15 V, V _{EE} = -15 V) T _A = +25°C T _A = -40° to +85°C (V _{CC} = 5.0 V, V _{EE} = 0 V) T _A = +25°C	17	I _{CC}	— — —	2.15 — —	2.75 3.0 2.75	mA


MC33272, MC33274

AC ELECTRICAL CHARACTERISTICS ($V_{CC} = +15 \text{ V}$, $V_{EE} = -15 \text{ V}$, $T_A = 25^\circ\text{C}$, unless otherwise noted.)

Characteristics	Figure	Symbol	Min	Typ	Max	Unit
Slew Rate ($V_{in} = -10 \text{ V}$ to $+10 \text{ V}$, $R_L = 2.0 \text{ k}\Omega$, $C_L = 100 \text{ pF}$, $A_V = +1.0 \text{ V}$)	18, 33	SR	8.0	10	—	$\text{V}/\mu\text{s}$
Gain Bandwidth Product ($f = 100 \text{ kHz}$)	19	GBW	17	24	—	MHz
AC Voltage Gain ($R_L = 2.0 \text{ k}\Omega$, $V_O = 0 \text{ V}$, $f = 20 \text{ kHz}$)	20, 21, 22	A_{VO}	—	65	—	dB
Unity Gain Frequency (Open-Loop)		f_U	—	5.5	—	MHz
Gain Margin ($R_L = 2.0 \text{ k}\Omega$, $C_L = 0 \text{ pF}$)	23, 24, 26	A_m	—	12	—	dB
Phase Margin ($R_L = 2.0 \text{ k}\Omega$, $C_L = 0 \text{ pF}$)	23, 25, 26	ϕ_m	—	55	—	Degrees
Channel Separation ($f = 20 \text{ Hz}$ to 20 kHz)	27	CS	—	-120	—	dB
Power Bandwidth ($V_O = 20 \text{ V}_{\text{p-p}}$, $R_L = 2.0 \text{ k}\Omega$, THD $\leq 1.0\%$)		BWP	—	160	—	kHz
Total Harmonic Distortion ($R_L = 2.0 \text{ k}\Omega$, $f = 20 \text{ Hz}$ to 20 kHz , $V_O = 3.0 \text{ V}_{\text{rms}}$, $A_V = +1.0$)	28	THD	—	0.003	—	%
Open-Loop Output Impedance ($V_O = 0 \text{ V}$, $f = 6.0 \text{ MHz}$)	29	$ Z_O $	—	35	—	Ω
Differential Input Resistance ($V_{CM} = 0 \text{ V}$)		R_{IN}	—	16	—	$M\Omega$
Differential Input Capacitance ($V_{CM} = 0 \text{ V}$)		C_{IN}	—	3.0	—	pF
Equivalent Input Noise Voltage ($R_S = 100 \Omega$, $f = 1.0 \text{ kHz}$)	30	e_n	—	18	—	$\text{nV}/\sqrt{\text{Hz}}$
Equivalent Input Noise Current ($f = 1.0 \text{ kHz}$)	31	i_n	—	0.5	—	$\text{pA}/\sqrt{\text{Hz}}$

2

**Figure 1. Equivalent Circuit Schematic
(Each Amplifier)**



MC33272, MC33274

2

Figure 2. Maximum Power Dissipation versus Temperature




Figure 3. Input Offset Voltage versus Temperature for Typical Units




Figure 4. Input Bias Current versus Common Mode Voltage




Figure 5. Input Bias Current versus Temperature




Figure 6. Input Common Mode Voltage Range versus Temperature





Figure 7. Open-Loop Voltage Gain versus Temperature



MC33272, MC33274

2

Figure 8. Split Supply Output Voltage Swing versus Supply Voltage




Figure 9. Split Supply Output Saturation Voltage versus Load Current




Figure 10. Single Supply Output Saturation Voltage versus Load Resistance to Ground




Figure 11. Single Supply Output Saturation Voltage versus Load Resistance to V_{CC}




Figure 12. Output Voltage versus Frequency





Figure 13. Common Mode Rejection versus Frequency



2

Figure 14. Positive Power Supply Rejection versus Frequency




Figure 15. Negative Power Supply Rejection versus Frequency




Figure 16. Output Short Circuit Current versus Temperature




Figure 17. Supply Current versus Supply Voltage




Figure 18. Normalized Slew Rate versus Temperature





Figure 19. Gain Bandwidth Product versus Temperature



MC33272, MC33274

Figure 20. Voltage Gain and Phase versus Frequency





Figure 21. Gain and Phase versus Frequency



2

Figure 22. Open-Loop Voltage Gain and Phase versus Frequency




Figure 23. Open-Loop Gain Margin and Phase Margin versus Output Load Capacitance




Figure 24. Open-Loop Gain Margin versus Temperature





Figure 25. Phase Margin versus Temperature



MC33272, MC33274

2

Figure 26. Phase Margin and Gain Margin versus Differential Source Resistance




Figure 27. Channel Separation versus Frequency




Figure 28. Total Harmonic Distortion versus Frequency




Figure 29. Output Impedance versus Frequency




Figure 30. Input Referred Noise Voltage versus Frequency





Figure 31. Input Referred Noise Current versus Frequency



MC33272, MC33274

2

Figure 32. Percent Overshoot versus Load Capacitance




Figure 33. Noninverting Amplifier Slew Rate for the MC33274




Figure 34. Noninverting Amplifier Overshoot for the MC33274




Figure 35. Small Signal Transient Response for MC33274




Figure 36. Large Signal Transient Response for MC33274

