

Common Mode Filters(SMD)

For USB / LVDS

TCM series

Type: TCM0806G [0302 inch]*

* Dimensions Code JIS[EIA]

Issue date: December 2010

[•] All specifications are subject to change without notice.

[•] Conformity to RoHS Directive: This means that, in conformity with EU Directive 2002/95/EC, lead, cadmium, mercury, hexavalent chromium, and specific bromine-based flame retardants, PBB and PBDE, have not been used, except for exempted applications.

ATDK

Common Mode Filters(SMD) For High-speed Differential Signal Line

Conformity to RoHS Directive

TCM Series TCM0806G Type

FEATURES

- The TCM0806G (L0.85×W0.65×T0.40mm) is an ultra-compact common mode filter that is in the smallest class in the industry.
- By providing wide bandwidth (cutoff frequency: 3GHz) for differential mode, this product has almost no effect for highspeed differential signals and can suppress the radiated emission.
- This product contains no lead and supports lead-free soldering.

APPLICATIONS

- High speed interface(LVDS, IEEE1394 and USB2.0) in electronics devices.
- Portable audio, digital cellular phones, DVC, DSC, PDP/LCD/ DLP/PJ TVs, DVD players, notebook PCs, amusement machines, etc.

PRODUCT IDENTIFICATION

TCM	0806	G -	900 -	· 2P	- T
(1)	(2)	(3)	(4)	(5)	(6)

- (1) Series name
- (2) Dimensions L×W
- (3) Product identification number
- (4) Impedance[at 100MHz] $900: 90\Omega$
- (5) Number of line 2P: 2-line
- (6) Packaging style
 T: ø180mm reel taping


TEMPERATURE RANGE

Operating	−25 to +85°C	

PACKAGING STYLE AND QUANTITIES


Packaging style	Quantity
Taping	10000 pieces/reel

SHAPES AND DIMENSIONS/CIRCUIT DIAGRAM/RECOMMENDED PC BOARD PATTERN





No polarity



ELECTRICAL CHARACTERISTICS

Common mode impedance (Ω) [100MHz]	DC resistance $(\Omega)[1 \text{ line}]$	Rated current Idc(A)max.	Rated voltage Edc(V)max.	Insulation resistance $(M\Omega)$ min.
35±30%	1.15±30%	0.10	10	10
65±20%	2.50±30%	0.10	10	10
90±20%	2.70±30%	0.10	10	10
	Common mode impedance (Ω) [100MHz] 35±30% 65±20% 90±20%	(Ω) [100MHz] (Ω)[1 line] 35±30% 1.15±30% 65±20% 2.50±30%	(Ω) [100MHz] (Ω)[1 line] Idc(A)max. $35\pm30\%$ $1.15\pm30\%$ 0.10 $65\pm20\%$ $2.50\pm30\%$ 0.10	(Ω) [100MHz] $(Ω)$ [1 line] Idc(A)max. Edc(V)max. 35±30% 0.10 10 65±20% 2.50±30% 0.10 10

- Conformity to RoHS Directive: This means that, in conformity with EU Directive 2002/95/EC, lead, cadmium, mercury, hexavalent chromium, and specific bromine-based flame retardants, PBB and PBDE, have not been used, except for exempted applications.
- All specifications are subject to change without notice.



TYPICAL ELECTRICAL CHARACTERISTICS IMPEDANCE vs. FREQUENCY CHARACTERISTICS

