

## Connectors



### Miniature Plugs & Jacks

#### 2.5 Dia.



HSJ1621



JXP2104



HSJ1816



HSJ1757

Various types are available such as 2.5 dia. jacks and 3.5 dia. jacks. Configured to be small, thin and multi-poles.

#### 2.5 dia. miniature Jacks

Poles	Model No.	Height	Remarks
3p	HSJ1621	3 mm	
3p+Outer ring (4P)	HSJ1671	3.3 mm	1 pole outer ring
4p	HSJ1816	3.7 mm	
4p+Outer ring (5P)	HSJ1817	3.7 mm	1 pole outer ring
4p+Outer ring (6P)	HSJ1757	3.7 mm	2 pole outer ring

#### 3.5 Dia.



HSJ1636



JXP2028



HSJ1828

#### 3.5 dia. miniature Jacks

Poles	Model No.	Height	Remarks
3p	HSJ1636	4.4 mm	
3p	HSJ1828	3.9 mm	



### Pin Jacks



JPJ1225



JPJ3911



JPJ1689



JPJ1139

#### Introduction

Various types are available such as pin jack only, multiple-jack type and combined type. Combine type is a jack board in which various types of connector such as pin jack, S-terminal and optical connector are integrated. It improves efficiency of design process and assembly process for customer's products.

#### Applications

TV sets, PDPs, DVDs, STBs, etc.

#### With D Connectors



JXT1151



JXT1160

#### With Y/C Connectors



JXT1043



JXT1112

#### Specifications

Contact Resistance	30 m max.
Insulation Resistance	100 M min. at 500 V DC
Dielectric Strength	500 V AC(r.m.s.) for 1 minute
Insertion Force	30 N max.
Withdrawal Force	1 N to 15 N