


Spade and Ring Series

Pre-Insulated

.300 Hook
 .020 Pre Tinned Brass
 22-18 AWG (Red)




STYLE AND DIMENSIONS	STUD	MAX. INSULATION DIAMETER			SEAM	UL	CSA	QUANTITY PER REEL	PART NUMBER
		.117	.147	.180					
	4	X			B	✓	✓	5000	50800-200
			X		B	✓	✓	4000	50800-200-8
				X	B	✓	*	4000	50800-200-8A
	6	X			B	✓	✓	5000	50808-200
			X		B	✓	✓	4000	50808-200-8
				X	B	✓	*	4000	50808-200-8A
	8	X			B	✓	✓	5000	50816-200
			X		B	✓	✓	4000	50816-200-8
				X	B	✓	*	4000	50816-200-8A

Spade and Ring Series

Pre-Insulated

.300 Hook
 .031 Electro-Tinned Copper
 22-18 AWG (Red)



STYLE AND DIMENSIONS	STUD	MAX. INSULATION DIAMETER			SEAM	UL	CSA	QUANTITY PER REEL	PART NUMBER
		.117	.147	.180					
	4	X			B	✓	✓	5000	50800-300
			X		B	✓	✓	4000	50800-300-8
				X	B	✓	*	4000	50800-300-8A
	6	X			W	✓	✓	5000	50801-300
			X		W	✓	✓	4000	50801-300-8
				X	W	✓	*	4000	50801-300-8A
	8	X			B	✓	✓	5000	50808-300
			X		B	✓	✓	4000	50808-300-8
				X	B	✓	*	4000	50808-300-8A
	8	X			W	✓	✓	5000	50809-300
			X		W	✓	✓	4000	50809-300-8
				X	W	✓	*	4000	50809-300-8A
	8	X			B	✓	✓	5000	50816-300
			X		B	✓	✓	4000	50816-300-8
				X	B	✓	*	4000	50816-300-8A
	8	X			W	✓	✓	5000	50817-300
			X		W	✓	✓	4000	50817-300-8
				X	W	✓	*	4000	50817-300-8A

Recommended Strip Length $\frac{3}{32} \pm \frac{1}{32}$
 * Contact Factory for Latest Agency Approvals.