

## Basic Rack PDU

### Rack PDU, Basic, Zero U, 20A, 120V, (14)5-15

**AP9551**
[✉ Email Technical Specifications](#)  
[🖨 Printer Friendly](#)



APC Basic Rack PDU , Input: 120V , Input Connections: NEMA L5-20P , Cord Length: 12 feet ( 3.66 meters ) , Output: 120V , Output Connections: NEMA 5-15R

**Includes:** Rack Mounting brackets, Toolless Mounting Kit, User Manual


**Standard Lead Time :** Usually in Stock

[+ More Images](#)
[Technical Specifications](#) | [Product Overview](#) | [Documentation](#) | [Options](#) | [Compare Models](#)

### Output

Nominal Output Voltage	120V
Maximum Total Current Draw per Phase	20A
Output Connections	(14) NEMA 5-15R 
Always on Outlets	14
Overload Protection	Yes

### Input

Nominal Input Voltage	120V
Input Frequency	50/60 Hz
Regulatory Derated Input Current (North America)	16A
Input Connections	NEMA L5-20P 
Cord Length	3.66 meters
Number of Power Cords	1
Acceptable Input Voltage	90-132 VAC
Maximum Line Current per phase	20A
Maximum Input Current per phase	20A
Load Capacity	2400 VA

### Physical

Net Weight	2.20 KG
Maximum Height	620.00 mm
Maximum Width	44.00 mm
Maximum Depth	44.00 mm
Shipping Weight	2.92 KG
Shipping Height	648.00 mm
Shipping Width	178.00 mm
Shipping Depth	152.00 mm
Color	Black
Units per Pallet	100.00

### Environmental

Operating Environment	0 - 45 °C
Operating Relative Humidity	0 - 95%
Operating Elevation	0-3000 meters
Storage Temperature	-25 - 65 °C
Storage Relative Humidity	0 - 95%
Storage Elevation	0-15000 meters

### Conformance

Regulatory Approvals	cUL Recognized,CSA,UL 1363,UL Recognized
Standard Warranty	2 years repair or replace