

USB 2.0 Hi-Speed A to Mini-B Cable (A to 4Pin Round Mini-B M/M) 6-ft.

MODEL NUMBER: **U029-006**



Description

Tripp Lite's 6-ft. gold USB 2.0 A /"Round" Mini-B 4-pin device cable Meets or Exceeds USB 2.0 Specifications. Connects a digital camera, PDA, cell phone, etc to a USB port on a computer or hub. Backward compatible - can be used with older USB 1.1 applications as well. All Tripp Lite USB 2.0 cabling include superior foil shielding for reliable, error-free data communications. The significantly faster data transfer rates of USB 2.0 (up to 480 Mbps) make them perfect for multimedia applications. Features gold-plated connectors and gold-plated copper contacts for superior conductivity. The cable is manufactured with molded connectors and integral strain relief for extra durability and long life.

Features

- Meets or Exceeds USB 2.0 Specifications
- Connects to Cameras, Cell Phones, PDA's, etc with 4-Pin "Round" Mini-B USB connectors
- Supports faster data transfer rate (1.5 to 480 Mbps) for low speed and high speed devices including multimedia applications
- Premium double-shielded cables with tinned copper braid and aluminum Mylar foil
- Gold plated connectors and gold plated copper contacts for superior conductivity.
- Molded connectors and integral strain relief for extra durability and long life.

Specifications

OVERVIEW	
Intended Application	Connecting Peripherals
Cable Type	USB

Highlights



- Meets or Exceeds USB 2.0 Specifications
- Connects to Cameras, PDA's, etc with "Round" Mini-B 4-Pin connectors

Applications

- This cable is compatible with the following digital camera models:
- **Kodak** C300, EasyShare Camera Dock, Camera Dock II, Camera Dock 6000, CX4200, CX4210, CX4230, CX4300, CX4310, CX6200, CX6230, CX6330, CX6445, CX7220, CX7300, CX7310, CX7330, CX7430, CX7525, CX7530, DC4800, DX3215, DX3500, DX3600, DX3700, DX3900, DX4330, DX4530, DX4900, DX6340, DX6440, DX6490, DX7440, DX7590, DX7630, LS420, LS443, LS633, LS743, LS753, Printer Dock 4000, Printer Dock 6000, Printer Dock Plus, Printer Dock, Z7590
- **Minolta** DiIMAGE 5, DiIMAGE 7, DiIMAGE 7A, DiIMAGE 7i
- **HP** 315, 315xi --**Olympus** E-10, E-20, C-2100UZ, C-3040Z, C-3030Z, C-700 UZ --**Sony** DSC-S70, DSC-S30
- **Epson** PhotoPC 3000Z and 3100Z --**HP** 315, 315xi

System Requirements

- Any USB device requiring a USB cable with Round Mini-B 4-Pin connector
- USB2.0 performance only when used with USB2.0 device and USB2.0 controller

INPUT	
Cable Length (ft.)	6
Cable Length (m)	1.83
UPC ASSIGNMENT	
Unit Carton UPC#	037332138941
PHYSICAL	
Color	Black
Style	USB
CONNECTIONS	
Connector A	 USB A (MALE)
Connector B	 USB MINI-B 4-PIN (MALE)
Number of Connectors	2
CERTIFICATIONS	
Certifications	USB-if 2.0 Approved
WARRANTY	
Product Warranty Period (Worldwide)	Lifetime limited warranty

Package Includes

- 6ft USB 2.0 A to "Round" 4-pin Mini-B Gold Cable

Related Items

Optional Products

Model Number	Description	Qty.
U022-006	6-ft. USB2.0 A/B Gold Device Cable (A Male to B Male)	1
U022-010	10-ft. USB2.0 A/B Gold Device Cable (A Male to B Male)	1
U024-006	6-ft. USB A/A Gold Extension Cable for USB2.0 Cable (USB-A M/F)	1
U024-010	10-ft. USB A/A Gold Extension Cable for USB2.0 Cable (USB-A M/F)	1
U028-006	6-ft. USB2.0 A to Mini-B Gold Device Cable (A Male to 4Pin Mini-B Male)	1



U030-006	6-ft. USB2.0 A to Mini-B Gold Device Cable (A Male to 5Pin Mini-B Male)	1
U209-000-R	USB to Serial Adapter (USB-A Male to DB9M)	1
U222-004-R	4-Port USB2.0 Ultra-Mini Hub	1

More information, including related products, owner's manuals, and additional technical specifications, can be found online at:

<http://www.tripplite.com/sku/U029-006>.

© 2014 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Tripp Lite:](#)

[U029-006](#)