



UM SERIES CHART 1  
 PAGE 1 OF 2  
 RELEASE NO. PR-19771  
 REPLACES  
 DRAWING NUMBER  
 ISSUE 12  
 CHECK  
 REVISIONS  
 A C094774 TSM 12 JUL 99  
 B 207494 SCL 19 FEB 03  
 C 207587 C S 5 MAR 03  
 D 207632 TSM 12 MAR 03  
 E 0000545 C S 16 JUN 03  
 CHECK  
 12 JUL 99  
 JAF  
 PTC/CAD 2D  
 TSM  
 12 JUL 99  
 CHECK  
 JAF

NOTES  
 1 MOUNTING HOLES WILL ACCEPT PINS OR SCREWS OF  $\varnothing 2.21/\varnothing .087$  MAX ON  $9.50 \pm 0.05/.374 \pm .002$  CENTERS  
 2 - TERMINALS ARE PLATED FOR SOLDERING  
 3 - SWITCH WILL WITHSTAND A TEMPERATURE OF  $82.2^\circ\text{C}/180^\circ\text{F}$

2158 4275.5-4401-1700/A1  
 9222145  
 E 12252  
 LR23413-167M  
 CE LISTING ELECTRICAL  
 PREFIX RATING  
 UM50 5A 250 VAC  
 UM40 3A 250 VAC  
 UM10 .1A 250 VAC  
 ANSI Y14.5M-1982 APPLIES

THIS DRAWING COVERS A PROPRIETARY ITEM AND IS THE PROPERTY OF MICRO SWITCH, A DIVISION OF HONEYWELL. THIS DRAWING IS NOT TO BE COPIED OR USED WITHOUT THE APPROVAL OF MICRO SWITCH.  
**MICRO SWITCH**  
 a Honeywell Division  
**SWITCH - BASIC**  
 CATALOG LISTING  
**UM SERIES CHART 1**  
 FED. MFG. CODE 91929

THIRD ANGLE PROJECTION  
 SCALE 4 : 1  
 DO NOT SCALE PRINT  
 TOLERANCES  
 APPLY TO DESIGN UNITS. CONVERSIONS ARE ONLY FOR REFERENCE. UNLESS NOTED, TOLERANCES ARE :  

DIM.	TOL.	DIM.	TOL.
mm	mm/100	"	mm/100
NO PLACES	X	1/100	X.X
ONE PLACE	X.X	0.4/0.016	X.XX
TWO PLACES	X.XX	0.15/0.006	X.XXX
THREE PLACES	X.XXX		X.XXXX

 SI METRIC  US CUSTOMARY   
 DESIGN UNITS  WEIGHT

