

## LT-LED LT-LED MV and LT-LED 110/230V



CE – certified to EMC directive 2004/108/EC.  
 Complies with low voltage directive 2006/95/EC.  
 High voltage transient and polarity reversal protected.  
 Operating temperature: -20°C to + 55°C.



|                        |                           |                                  |            |      |        |
|------------------------|---------------------------|----------------------------------|------------|------|--------|
|                        |                           |                                  |            |      |        |
| <b>Mains 110/230V</b>  | amber > 6cd<br>red > 10cd | 65 flashes/min<br>6 bursts/flash | 85–265 Vac | IP67 | 148gms |
| <b>Multivoltage MV</b> |                           |                                  | 10–100Vdc  |      |        |

### Features:

A compact LED beacon with low power consumption.

- Multivoltage 10–100Vdc, and mains 110Vac and 230Vac versions
- Flashing and continuously lit modes
- Clear lens with coloured LEDs
- Low power consumption
- 3 year guarantee
- Weatherproof to IP67

### Materials:

Polycarbonate lens and base. ROHS compliant.

### Accessories:

**FX2**  
mounting  
base



**FX40**  
mounting  
bracket



**FX39**  
mounting  
pole



| Product                | <i>i</i> flashing  | <i>i</i> constant   | Amber  | Red    |
|------------------------|--|---|--------|--------|
| <b>Mains 110/230V</b>  | 15mA @ 110Vac<br>10mA @ 230Vac                                 |   | 448002 | 448003 |
| <b>Multivoltage MV</b> | 110mA @ 12Vdc<br>55mA @ 24Vdc<br>35mA @ 50Vac<br>25mA @ 100Vac | 80mA @ 12Vdc<br>40mA @ 24Vdc<br>25mA @ 50Vac<br>20mA @ 100Vac | 446002 | 446003 |

  

|  |
|--|
|  |
|--|