



- NOTES:
1. ALL DIMENSIONS IN MM [INCH]
 2. GENERAL TOLERANCE: x.x=±0.4mm
x.xx=±0.25mm
 3. RATING: DC 30V, 0.3A
 4. OPERATING FORCE: 200±100gf
 5. TRAVEL: 3.3mm FULL TRAVEL (B)
 6. LIFE CYCLES: 10,000 CYCLES
 7. OPERATING TEMPERATURE: -20°C TO 70°C
 8. CONTACT RESISTANCE: 20mΩ MAX. (B)
 9. INSULATION RESISTANCE: 100MΩ MIN@ 500VDC.
 - ▲ 10. LED COLOR: GREEN
 11. ▲ DENOTES CRITICAL PARAMETER.
 12. 2002/95/EC (RoHS) COMPLIANT.



▲ LED SPECS	UNITS	GREEN
FORWARD CURRENT	mA	20
FORWARD VOLTAGE @20mA	V	1.7 Typ-2.6 Max
LUMINOUS INTENSITY @ 10mA	MCD	4.7-7.8



B	19529	DRAWING UPDATE / CLEAN UP	12/14/10	BGL
A	18805	New-Release	1/20/10	rc
REV	PCR NO	DESCRIPTION	DATE	BY

TITLE WBL4UOAGQ				
SCALE	DATE	DR	DWG	REV
2	1/20/2010	rc	B400004	B

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED