

Precision SMA Female to 7mm Sexless Adapter



**PE9214** 

## **TECHNICAL DATA SHEET**

Configuration	
Connector 1	SMA Female
Connector 2	7mm Sexless
Adapter Design	Precision
Body Style	Straight
Electrical Specifications	
Frequency Range, GHz	DC to 18
Impedance, Ohms	50
Maximum VSWR	1.15:1
Mechanical Specifications	
Size	
Length, in [mm]	1.195 [30.35]
Width/Dia., in [mm]	0.87 [22.1]
Dielectric Type	PTFE
Connector 1	
Туре	SMA Female
Inner Conductor Material and Plating	Beryllium Copper, Gold
Inner Conductor Plating Specification	MIL-G-45204
Body Material and Plating	Stainless Steel, Passivate
Body Plating Specification	ASTM A380
Connector 2	
Туре	7mm Sexless
Inner Conductor Material and Plating	Beryllium Copper, Gold
Inner Conductor Plating Specification	MIL-G-45204
Body Material and Plating	Stainless Steel, Passivate
Body Plating Specification	ASTM A380
Compliance Certifications (visit www.Pasternack.c	
RoHS Compliant	Yes
Plotted and Other Data	
Notes:	Values at 25 °C, sea leve
URL: http://www.pasternack.com/sma-female-7mm	-sexless-straight-adapter-pe9214-p.as

Precision SMA Female to 7mm Sexless Adapter from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and fiber optic products maintain a 99% availability and are part of the broadest selection in the industry.

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.

Pasternack Enterprises, Inc. • P.O. Box 16759, Irvine, CA 92623 **Phone:** (866) 727-8376 or (949) 261-1920 • **Fax:** (949) 261-7451 Sales@Pasternack.com • Techsupport@Pasternack.com



## PE9214 CAD Drawing

Precision SMA Female to 7mm Sexless Adapter

