

# ICO-200

Embedded Field Controller with AMD Geode™ LX800 Onboard and Front Cabling



▲ Front view



IP40 Fanless Low Power

## Specifications

Standard Color	White
Construction	Aluminum & heavy-duty steel, IP40
CPU	AMD Geode™ LX800 500 MHz processor onboard
System Board	SBC84620
System Memory	1 x 200-pin DDR SO-DIMM max. up to 1 GB
BIOS	Phoenix-Award 4Mbit with RPL/PXE LAN Boot ROM SmartView and customer CMOS backup
System I/O Outlet	1 x RS-232 or RS-485 (COM 1) 1 x RS-232/422/485 (COM 2) 1 x VGA 1 x PS/2 keyboard/mouse 2 x 10/100Mbps Ethernet 2 x USB 2.0 1 x VDC power input connector
Watchdog Timer	Reset supported; 255 level
Storage	Supports 1 x CompactFlash™
Installation	Din-rail
System Indicator	1 x green LED for system power-on 1 x orange LED for HDD active
Power Supply	24VDC
Dimensions	160.5 mm (6.32") (W) x 111.8 mm (4.40") (D) x 53.35 mm (2.10") (H)
Weight (net/gross)	1.2 kg (2.64 lb)/1.92 kg (4.23 lb)
EOS Support	XPE, WinCE, Linux
ISO	Manufactured in an ISO9001 facility
Environment	Operation temperature: 0°C ~ +50°C (+32°F ~ +122°F), Relative humidity: 10% ~ 95% @ 40°C ; non-condensing Operation vibration: 2 G, 5 ~ 500 Hz, random for CompactFlash™
Certification	CE

## Power Protection

### DC Version

OVP (over voltage protection)  
UVP (under voltage protection)  
Reverse protection

## Features

- Fanless cooling system: AMD Geode™ LX800 onboard
- Ultra slim and compact design
- Easy-to-maintain design: CF card, memory, mini-PCI
- Supports one CompactFlash™



▲ Din-rail mounting

## Ordering Information

### Standard

ICO-200	Embedded field controller with AMD Geode™ LX800 CPU onboard and front cabling
---------	---

### Optional

DDR SODIMM	256 MB ~ 1 GB
CompactFlash™	1 GB or above

\*Specifications and certifications are based on options and may vary.

## Dimensions

