

## SMA Female Right Angle Connector Solder Attachment 4 Hole Panel Solder Cup Terminal, .340 inch Hole Spacing



## **TECHNICAL DATA SHEET**

**PE4123** 

SMA Female Right Angle Connector Solder Attachment 4 Hole Panel Solder Cup Terminal, .340 inch Hole Spacing

## Configuration

Connector

Connector Interface Type
Cable Attachment Method (Shield/Contact)

Body Style

Mount Method

SMA Female
Solder Cup
Solder
Right Angle
4 Hole Panel

#### **Electrical Specifications**

Frequency Range, GHz DC to 18 Impedance, Ohms 50 Maximum VSWR 1.2:1

### **Mechanical Specifications**

#### Size

 Length, in [mm]
 0.685 [17.4]

 Width/Dia., in [mm]
 0.5 [13]

 Weight, lbs [g]
 0.013 [5.9]

 Mounting Hole Configuration
 A01

#### Connector

Type SMA Female
Contact Material and Plating Beryllium Copper, Gold
Contact Plating Specification MIL-G-45204
Body Material and Plating Stainless Steel
Dielectric Type Teflon

#### Compliance Certifications (visit www.Pasternack.com for current document)

RoHS Compliant Yes

#### **Plotted and Other Data**

Notes: Values at 25 °C, sea level

URL: http://www.pasternack.com/sma-female-standard-solder-cup-terminal-connector-pe4123-p.aspx

SMA Female Right Angle Connector Solder Attachment 4 Hole Panel Solder Cup Terminal, .340 inch Hole Spacing from Pasternack Enterprises has same day shipment for domestic and International orders. We maintain 99% availability of the industry's broadest selection of RF, microwave and fiber optic products.

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.



# PE4123 CAD Drawing

SMA Female Right Angle Connector Solder Attachment 4 Hole Panel Solder Cup Terminal, .340 inch Hole Spacing

