




- Single terminal for 6, 8, and 10 stud sizes
- Brazed Seam
- Chamfered Barrel
- Internal Barrel Serrations



Non-Insulated Multiple Stud Ring Terminals

Catalog Number	Wire Range	Bolt Size	Dimension inch mm						
			W	F	L	E	D	d1	T
K18-610MS-M	22-16 A.W.G. 0.5-1.5 mm ²	#6 - #10	.339 8.6	.311 7.9	.768 19.5	.189 4.8	.134 3.4	.067 1.7	.030 0.75
K14-610MS-M	16-14 A.W.G. 1.5-2.5 mm ²	#6 - #10	.339 8.6	.311 7.9	.768 19.5	.189 4.8	.161 4.1	.091 2.3	.031 0.8
K10-610MS-M	12-10 A.W.G. 4-6 mm ²	#6 - #10	.390 9.9	.350 8.9	.886 22.5	.236 6.0	.220 5.6	.134 3.4	.039 1.0

Box Quantity: (M)=1000

For Mylar Tape replace box quantity with (T). Example: K18-610MS-T

UL File #E9809

CSA File #LR4503

Terminal Material: Copper

See pages in back of catalog for complete tool information.

Tool and Die Selection Chart on page M42.

Tools used with Non-Insulated Multiple Stud Ring Terminals



ERG2002



KT-2500