

## SmartRack 18U Slim Wall-Mount Standard-Depth Rack Enclosure Cabinet

MODEL NUMBER: **SRW18US13**



### Highlights

- Slim design for shallow network switches and patch panels
- 18U with dual threaded front rails
- Locking, reversible front door
- Hinged cabinet swings away from wall bracket for easy equipment access (swing direction is reversible)
- Fully assembled for quick installation
- PCI-Compliant: meets stringent physical security requirements
- Interior vertical posts have square holes for cage nuts plus 12-24 threaded mounting holes

### Package Includes

- SRW18US13 Wall-Mount Rack Enclosure
- Mounting Hardware
- Keys
- Owner's Manual

### Description

The SRW18US13 slim 18U Wall-Mount Rack Enclosure is designed to safely store shallow network switches and patch panels. It integrates wall-mounting, easy equipment access and cable management in Telco environments with limited floor space. Ventilated top and bottom panels allows generous airflow to keep equipment operating safely. Top panel offers a convenient cable access cutout with cover. Adjustable front mounting rails have square holes (default position) and tapped holes to accommodate 18U of equipment. A sturdy hinge between the cabinet and the wall-mount bracket allows the cabinet to swing away from the wall for easy access to equipment and cabling. Supports up to 250lbs of equipment. The SRW18US13 comes with a 5-year product warranty.

### Features

- 18U slim wall-mounted enclosure
- Dual threaded rail option
- Ventilated top and bottom panels for increased airflow
- Locking, reversible front door
- Hinged cabinet swings away from wall bracket for easy equipment and cable access
- Fully assembled for quick installation
- PCI-Compliant: meets stringent physical security requirements

## Specifications

PHYSICAL	
Installed Whole System Maximum Rack Depth (in.)	13
Installed Whole System Maximum Rack Depth (cm)	33.02



**Tripp Lite**  
1111 W. 35th Street  
Chicago, IL 60609 USA  
Telephone: 773.869.1234  
www.tripplite.com

Rack Height (U Spaces)	18
Shipping Dimensions (hwd / in.)	41.61 x 25.6 x 14.96
Shipping Dimensions (hwd / cm)	105.68 x 65.02 x 37.99
Shipping Weight (lbs.)	98
Shipping Weight (kg)	44.45
Unit Dimensions (hwd / in.)	35.6 x 23.62 x 13
Unit Dimensions (hwd / cm)	90.42 x 59.9 x 33.02
Unit Weight (lbs.)	83.77
Unit Weight (kg)	38.00
Color	Black
Weight Capacity - Stationary (lbs.)	250
Weight Capacity - Stationary (kg)	113.40
Cable Access Hole Measurement (inches)	9.812 x 2.35 (l x w)
Hinged (Swings Away from Wall Bracket)	Yes
<b>SPECIAL FEATURES</b>	
Grounding Lug	Front door frame
Seismic Rack	No
<b>CERTIFICATIONS</b>	
Certifications	EIA-310-E
NOM (Mexico)	Tested to NOM (Mexico)
Approvals	RoHS
<b>WARRANTY</b>	
Product Warranty Period (Worldwide)	5-year limited warranty

© 2015 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies:

<http://www.tripplite.com/products/product-certification-agencies>