



- NOTES:
1. ALL DIMENSIONS IN MM [INCH]
  2. GENERAL TOLERANCE: X.X=±0.4 X.XX=±0.25
  3. TERM. NOS. FOR REF. ONLY
  4. RATING: 0.4VA @ 20V AC or DC max.
  5. FIXED TERM. MOVING CONTACT: COPPER ALLOY with GOLD Plate over Nickel plate
  6. ELECTRICAL LIFE: 50,000 make-and-break cycle at full load.
  7. DIELECTRIC STRENGTH: 1,000 V RMS @sea level.
  8. OPERATING TEMP.: -30°C to 85°C
  9. ▲ DENOTES CRITICAL PARAMETER.
  10. 2002/95/EC (ROHS) COMPLIANT

|      |         |  |          |      |                             |         |    |         |     |
|------|---------|--|----------|------|-----------------------------|---------|----|---------|-----|
| D    | 16058   | EDIT DIMENSIONS  | 5/30/06  | CT   |                             |         |    |         |     |
| C    | 12575   | CHANGE CAP PART NUMBER   | 12/14/04 | AR   |                             |         |    |         |     |
| B    | 14222   | REF. DIM WAS 6.51  | 8/11/04  | AR   |                             |         |    |         |     |
| A    | 13571   | RELEASED FOR PRODUCTION  | 11/3/03  | AR   |                             |         |    |         |     |
| REV. | ECN No. | DESCRIPTION  | DATE     | CHKD | SCALE                       | DATE    | DR | DWG     | REV |
|      |         | THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED |          |      | 2:1                         | 11/3/03 | AR | XT0121P | D   |
|      |         |  |          |      | <b>E-SWITCH®</b>            |         |    |         |     |
|      |         |  |          |      | TITLE<br>800AWS P8M7REC2BLK |         |    |         |     |